

tessera® arran

A luxurious heavyweight carpet tile designed for commercial, recreational and hospitality interiors, Arran takes the concept of linearity into an unusual new direction. Far from being formal and regimented, this floor covering is rugged, undulating and rich with visual interest and texture.

Arran's natural, almost 'artisan' appearance belies the complexity of its multi-height textured loop pile design and the state of the art manufacturing technology behind it. Using CMC Infinity machinery Forbo's designers have developed a carpet tile with unashamedly irregular peaks and furrows which broadlooms beautifully to deliver an alluringly tactile linear design offering real warmth.

Arran is offered in a broad range of eighteen colourways comprising natural and more vibrant tones to complement today's most contemporary interior environments. Each tile features a carefully blended duo of yarns, 100% solution dyed to ensure the subtle colour contrasts are maintained throughout the lifespan of the flooring, even in the most demanding environments subjected to intensive cleaning regimes.

For the ultimate in underfoot comfort, warmth, performance longevity and acoustic insulation, Arran can be installed with Softbac® backing, which will extend the standard ten year guarantee by five years.



Colour: 1517 umber & 1511 coffee laid linear

Orientation to suit your needs

Through the use of CMC technology, Arran has been cleverly designed to allow you to create two two effects can be created by using the same very different appearance finishes. Whether you are after a high design linear effect, or a rugged textural look, Arran carpet tiles can easily and stylishly meet your needs.

Arran avoids the market place 'norm' of high contrast colours to create the look of texture and instead boasts a broad tone-on-tone colour bank.



Colour: 1517 umber & 1511 coffee laid textural

Creating the designs

By simply changing the orientation of the fitting,

Both 'looks' are laid in a broadloom fashion, but are either laid across the main direction of traffic, or with the main direction of traffic as shown above.

Technical specifications

Arran carpet tiles meet the requirements of EN 1307

(7)n	Desertion to fine	EN 13501 1	D -1	
	Arran carpet tiles meet th	e requirements of EN 1	4041 EN 14	
\bigoplus	Installation method		Broadloom, tessellated or quarter turn	
10	Guarantee		Arran carpet tiles are guaranteed for 10 years under heavy contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.	
	Environmental		Materials used in the construction of Tessera carpet tiles are chosen for their low volatile organic compound (VOC) levels. Arran carpet tiles are manufactured using 100% green electricity.	
(K 2)	Dimensional stability	EN 986	≤0.2%	
	Light fastness	EN ISO 105 B02	≥5	
	Castor chair use	EN 985	Minimum R value: ≥2.4 Overall R value: 2.9	
	Secondary backing		Modified bitumen and polyester fleece. Also available in SOFTbac® secondary backing	
	Primary backing		Polyester	
	Total weight		4,565 gsm ± 10%	
2	Pile weight		950 gsm ± 10%	
	Stitch density		203,097 per m² ± 10%	
	Dye method		100% solution dyed	
	Pile composition		100% Invista Antron Lumena	
	Application (Class 33)	EN 1307	Class 33, Suitable for any type of heavy contract application	
	Collection size		18 colourways 4m² per box	
	Pile height		4.0mm ± 0.5mm	
Ť	Total thickness		7.5mm ± 10%	
	Dimensions		50cm x 50cm (Other sizes available for special orders)	
	Description		Tufted multi-pile height loop carpet tile	
	Affair curper tiles meet the requirements of EN 1507			

	Arian carpet tiles meet tile requirements of tiv 14041			
Barat	Reaction to fire	EN 13501-1	B _{fl} -s1	
	Slip resistance	EN 13893	DS: ≥0.30	
24	Electrical resistance	EN 10965 & EN1815	<1 x 10° Ω: Static dissipative. Body voltage: Pass (< 2kV)	

Installation and Maintenance

Shades may vary from batch to batch and should be checked before installation. Batches should not be mixed in the same location. All Tessera products are to be installed in full accordance with Forbo installation instructions and recognised

Regular power vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth or, for more resistant stains, with a mild detergent solution. For full installation and cleaning and maintenance instructions please go to www.forbo-flooring.co.uk

Service Products

Forbo Ireland Ltd

Tel: 00353 1 2898 898

Fax: 00353 1 2898 177 Email: info.ireland@forbo.com

www.forbo-flooring.ie

Blackrock

Co Dublin

2 Deansgrange Business Park

As a total flooring solutions provider, Forbo Flooring Systems provides a full range of products specially designed to support the installation of our floor coverings. For more information on these products, please contact your local Forbo Business Area Manager or visit www.forbo-flooring.co.uk

Our recommended adhesive for our collection of Tessera carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information. Forbo Flooring Systems reserves the right to improve the specification of its products without giving

Forbo Flooring UK Limited PO Box 1, Kirkcaldy, Fife KY1 2SB

London EC1 showroom

79 St. John Street, Clerkenwel London FC1M 4NR Tel: 0207 553 9300

For commercial enquiries: If calling from the North,

Midlands, London & South East Tel: 0800 0282 162 Fax: 01772 646 912 If calling from Scotland & South West

Tel: 0800 0935 258 Fax: 01592 643 999 Nuway enquiries:

Tel: 01773 740 688 Fax: 01773 740 640

Residential enquiries: Tel: 0800 0935 846

Fax: 01592 643 999 Email: info.flooring.uk@forbo.com www.forbo-flooring.co.uk

Samples: Tel: 0800 731 2369

Registered office:

Forbo Flooring UK Limited Den Road, Kirkcaldy Registered in Scotland: No 41400











Orientation to suit your needs





April 2011

tessera[®] arran



1502 danube laid textural 1500 olive laid textural