



## westbond® natural

### Undyed British wool ensuring natural colours

Westbond Natural is a unique collection of commercial carpet tiles containing pure and natural undyed wool. The range is the perfect answer to today's ecological concerns.

The carpet tile backing minimises environmental impact through its use of up to 74% recycled materials and wool is a sustainable, natural and renewable resource.

The colours are derived from a blend of fleeces from seven different UK sheep breeds, Herdwick, Swaledale, Shetland, The Derbyshire Gritstone, The Jacob, Dales Bred and Cheviot, resulting in a warm palette of taupes, creams, beiges and umber.

### What to do next

To request a sample of Westbond Natural please ring **0800 731 2369** or contact your local Forbo Business Area Manager.

For information on other flooring products available from Forbo Flooring Systems, please call customer services on **0800 0282 162**, email [info.flooring.uk@forbo.com](mailto:info.flooring.uk@forbo.com) or visit [www.forbo-flooring.co.uk](http://www.forbo-flooring.co.uk)




2400gsm honiton

### Technical specifications

Natural carpet tiles meet the requirements of EN 1307

Description	Fusion bonded cut pile carpet tile	
Dimensions	50cm x 50cm	
Total thickness	9mm / 16mm ± 10%	
Pile height	7mm / 14mm ± 0mm -0.5mm	
Collection size	13 colourways 4.5m <sup>2</sup> / 2.5m <sup>2</sup> per box	
Application (Class 32)	EN 1307	Class 32, Suitable for general commercial applications
Pile composition	80% Undyed British wool / 10% polyamide / 10% polyester	
Dye method	Blended Wool (undyed)	
Pile density	0.170 / 0.170 grams per cm <sup>3</sup>	
Tuft density	366,000 / 366,000 per m <sup>2</sup> ± 10%	
Pile weight	1,200 / 2,400 gsm ± 10%	
Total weight	4,300 / 5,400gsm ± 10%	
Tile backing	PVC incorporating up to 74% pre-consumer recycled content	
Castor chair use	EN 985	Minimum R value: ≥ 2.4
Light fastness	EN ISO 105 B02	≥ 5
Dimensional stability	EN 986	≤ 0.2%
Environmental	Materials used in the construction of Westbond carpet tiles are chosen for their low volatile organic compounds. Westbond carpet tiles are made using 100% Green electricity. All Westbond carpet tiles utilise a mixed vinyl waste backing which contains up to 74% pre-consumer recycled content in order to minimise environmental impact. The process uses existing Forbo technology which accesses PVC waste streams from a number of our factories, and also those of competitors within the flooring industry, thereby decreasing the amount of waste material which would otherwise be sent to landfill. Westbond products meet the 01350 indoor air quality standard. Forbo Flooring UK Ltd is a member of Carpet Recycling UK.	
CRI	CRUK	
Guarantee	Westbond Natural carpet tiles are guaranteed for 7 years under general contract use.* <i>*Provided that the carpet tiles have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.</i>	
Installation method	Broadloom, tessellated or quarter turn	

Natural Fusion bonded products meet the requirements of EN 14041

Reaction to fire	EN 13501-1	C <sub>fl</sub> -s1	 EN 14041
Slip resistance	EN 13893	DS: ≥ 0.30	
Electrical resistance	EN 10965 & EN1815	<1 x 10 <sup>9</sup> Ω: Static dissipative. Body voltage: Pass (< 2kV)	

### Installation and Maintenance

Shades may vary from batch to batch and should be checked before installation. Batches should not be mixed in the same location. All Westbond products are to be installed in full accordance with Forbo installation instructions and recognised trade standards.

Regular power vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth or, for more resistant stains, with a mild detergent solution. For full installation and cleaning and maintenance instructions please go to [www.forbo-flooring.co.uk](http://www.forbo-flooring.co.uk)

### Service Products

As a total flooring solutions provider, Forbo Flooring Systems provides a full range of products specially designed to support the installation of our floor coverings. For more information on these products, please contact your local Forbo Business Area Manager or visit [www.forbo-flooring.co.uk](http://www.forbo-flooring.co.uk)

Our recommended adhesive for our collection of Westbond carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

Forbo Flooring Systems reserves the right to improve the specification of its products without giving prior notice. Errors and omissions excepted.

### UK

Forbo Flooring UK Limited  
PO Box 1, Kirkcaldy, Fife KY1 2SB

### London EC1 showroom

79 St John Street, Clerkenwell  
London EC1M 4NR  
Tel: 0207 553 9300

### For commercial enquiries:

If calling from the North, Midlands, London & South East  
Tel: 0800 0282 162  
Fax: 01772 646 912

If calling from Scotland & South West

Tel: 0800 0935 258  
Fax: 01592 643 999

### Nuway enquiries:

Tel: 01773 740 688  
Fax: 01773 740 640

### Residential enquiries:

Tel: 0800 0935 846  
Fax: 01592 643 999

Email: [info.flooring.uk@forbo.com](mailto:info.flooring.uk@forbo.com)  
[www.forbo-flooring.co.uk](http://www.forbo-flooring.co.uk)

### Samples:

Tel: 0800 731 2369

### Ireland

Forbo Ireland Ltd  
2 Deansgrange Business Park  
Blackrock  
Co Dublin

Tel: 00353 1 2898 898  
Fax: 00353 1 2898 177  
Email: [infoireland@forbo.com](mailto:infoireland@forbo.com)  
[www.forbo-flooring.ie](http://www.forbo-flooring.ie)

### Registered office:

Forbo Flooring UK Limited  
Den Road, Kirkcaldy  
Fife KY1 2ER  
Registered in Scotland: No 41400



CI/SIB  
(43) | Tn6 |  
May 2011



creating better environments

westbond®  
carpet tiles

westbond®  
carpet tiles

natural

natural



CARPET TILES



CARPET TILES

CI/SIB  
(43) | Tn6 |  
May 2011



FLOORING SYSTEMS

forbo



**westbond**<sup>®</sup> carpet tiles

**natural**