# **EXPONA DESIGN STONE & EFFECT PUR**

- Expona Design PUR collection
- Authentic reproductions of classic and contemporary materials
- Ideal for very heavy commercial interiors
- Premium collection of Luxury Vinyl Tiles featuring exclusive and innovative stones and effects

# SPECIFICATION







0.7mm



16 @ 457 x 457mm = 3.34m<sup>2</sup>

18 @ 305 x 610mm = 3.34m<sup>2</sup>

12 @ 305 x 914mm = 3.34m<sup>2</sup>

8 @ 457 x 914mm = 3.34m<sup>2</sup>



5100a/m<sup>2</sup>



**GENERAL PERFORMANCE** 

EN 649 EN ISO 10582









**REACTION TO FIRE** 

EN ISO 13501-1 Class BfI-S1



SLIP RESISTANCE Class DS (dry condition)

**DIN 51130** R10 AS/NZS 4586 R10

For safety flooring with sustainable wet slip resistance, refer to Expona Control or the Polysafe ranges



**LIGHT FASTNESS** 

ISO 105-B02 Method 3 ≥6



ABRASION RESISTANCE

EN 649 Group T EN ISO 10582 Type 1



### **ELECTRICAL BEHAVIOUR (body voltage)**

EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



**INDENTATION - RESIDUAL** 

EN 433 0.05mm EN ISO 24343-1 0.05mm



# **DIMENSIONAL STABILITY**

**EN 434**  $\leq$  0.1% max. EN ISO 23999 ≤ 0.1% max.



CASTOR CHAIR (continuous use)

EN 425/ISO 4918 Suitable



### THERMAL CONDUCTIVITY

Suitable for underfloor heating Max. 27°c



#### **VOC EMISSIONS**

Indoor Air Comfort GOLD - Eurofins certified product

AgBB - Very low emissions

Swedish BPD (FLEC Test) - Best Class Afsset A+

FloorScore - Certified product Finnish M1 - Pass



# **ENVIRONMENTALLY PREFERABLE FLOORING**

Expona Design PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429). EN 15804 Environmental Product Declaration (EPD) is available on request. Expona Design PUR is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



#### **APPLICATIONS**

Expona Design PUR is ideal for very heavy commercial areas within the retail, office, leisure, healthcare, education and housing sectors.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128 bames Halstead EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WEBSITE: WWW.POLYFLOR.COM









# STONE & EFFECT



PERFORMANCE AND **PROPERTIES** 





