
French Doors and Sliding Patio Doors





SPECIFICATIONS

Sliding Door:

Heads and Stiles 91x56mm Bottom rail 91x56mm

Sliding Frame: Heads and Jambs 143x56mm 143x56mm Sole

French Style (Open Out):

Heads and Stiles 118x56mm Bottom rail 162x56mm

French Style Frame: 93x56mm Heads and Jambs Sole Aluminium

SIZES

Can be manufactured within the following width parameters:

Slidina:

1,500mm (min.) - 2,900mm (max.) French Style:

1,200mm (min.) - 2,000mm (max.) However, the following standard

systems are available:

Sliding:

1,800mm x 2,100mm & 2,400mm x 2,100mm French Style:

1,500mm x 2,100mm & 1,800 x 2,100mm





Allan Brothers Limited Allan House, Ord Road, Berwick-Upon-Tweed, TD15 2XU Telephone: 01289 334 600 Fax: 01289 334 601 www.allanbrothers.co.uk

CONSTRUCTION

Manufactured as standard from laminated redwood, selected for its durability and attractive appearance, these doors combine good looks with peace of mind.

Alternatively, if required, the door and frame can be made from quality hardwood.

All timbers are preservative treated after all machining in accordance with BS8417.

As standard we supply special low level thresholds for wheelchair access in accordance with: Approved Document M England & Wales and the Scottish Building Standards - Section 4. Alternative threshold options are available to suit most situations.

GLAZING

Both door systems have 40 x 20mm glazing rebates to ensure that the 22mm (4/14/4) Sofcoat 'Low E' toughened glazing units, which are fitted as standard, have adequate ventilation around their perimeters. Specialist glass units, including leaded, Georgian bar can be fitted upon request.

The beading is secured using Allan Brothers' fixing system to enhance product integrity and appearance.

PERFORMANCE

These doors are designed to cope with adverse weather conditions without compromising on stylish good looks. At the heart of both systems are 56mm finished thickness, weather-stripping and multipoint espagnolette locking. This gives robustness, stability and a high level of resistance to forced entry. Glazing is drained and vented as standard.

IRONMONGERY

Sliding Doors: All are supplied as standard with a brown lever lock handle set, euro cylinder lock barrels, four-point espagnolette locking and anti-lift device. Alternative handle finishes are available on request.

French Style Doors: Doors that open out are supplied as standard. Doors that open in can be supplied on request. Brass handles, escutcheon and euro cylinder lock barrels are fitted as standard, as are concealed three-point espagnolette locking, with dead bolt and concealed slip bolts to the fixed leaf. Alternative handle finishes are available upon request. Hinges are fully adjustable.

FACTORY FINISH

Allan Brothers' products are treated with preservative after all machining. This is applied by means of a double vacuum process in accordance with BS8417 and NHBC recommendations. Our water-based coatings are carefully formulated to seal the endgrain against moisture ingress, inhibit tannin stain and give the timber a quality look and feel.

SECURITY


Sliding Doors: The combination of double rebated frame sections, double gaskets, four point espagnolette locking, anti-lift device and security glazing makes these doors highly resistant to forced entry.

French Style Doors: The combination of 56mm finished thickness security hinges, concealed three-point espagnolette with dead bolt, concealed slip bolts to the fixed leaf and security glazing ensures these doors are also highly resistant to forced entry.

OTHER TECHNICAL INFORMATION

Allan Brothers provide a full technical back-up service covering all aspects of product and glazing performance.

Technical information, including detailed drawings, guidelines for installation and storage and operating and maintenance instructions, is available on request.



NB: Section drawings herein are not to scale

@Allan Brothers Ltd. All rights reserved. No part of this brochure may be reproduced without prior written permission. This brochure is an invitation to treat. Whilst every care is taken in the production of this brochure. Allan Brothers Ltd cannot be held responsible for any errors or omissions. The colour and



finishes within this brochure are as accurate as possible within the limitations of printing. In the interest of continuing design, development and product



improvements, we reserve the right to change colours, design and specification without prior notice





