

# floating floor treatments

## ACOUSTIC FLOORING SYSTEMS C30, CK30, C40 & C60

The versatile cradle and batten systems with their unique, patented, recycled, rubber crumb cradles comply with Robust Detail FFT2. Widely used for Pre-Completion Testing and in refurbishment and new build projects, these systems can be levelled on site to eliminate variations in the structural floor surface as well as accommodating services.



## COMPONENTS



www.instacoustic.co.uk Insta House, Ivanhoe Road Hogwood Business Park, Finchampstead Wokingham, Berks RG40 4PZ

## **APPLICATIONS**

- New build
- Robust detail FFT2
- Pre-completion testing
- Timber frame
- Floor levelling system
- Refurbishment / Change of use
- All concrete floors
- All Timber floors
- Access for services
- Sports halls

# floating floor treatments

## ACOUSTIC FLOORING SYSTEMS C30, CK30, C40 & C60

#### Multiple Cradle Base Packer assembly




### Increasing Floor Heights

When increased finished floor heights are required, to cater for specific design criteria, deep services or very uneven sub-bases, cradle base packers or deep cradle battens are available, for rapid, cost-effective height adjustment. The cradle base packers may be used in multiples to achieve the desired finished floor height. Deeper battens are generally used in larger projects and where a consistant high void is required.


19mm

43mm


20mr



#### 124mm finished floor heights



#### Interlocking Cradle Base Packer assembly for increased elevation



#### Deeper Cradle Battens for increased elevation

