

Folding walls Glass folding walls





Centrefold



Endfold

Folding walls

STYLEFOLD 120 - An easy to operate flush folding wall which can either be top hung from a ceiling track or supported by a low profile surface mounted floor track.

The wall is fitted with double PVC seals all round to ensure a high level of acoustic integrity is achieved and maintained between adjacent rooms.

Supplied as either a centrefold or endfold configuration to accommodate different parking requirements. All panels are continuously hinged and the end panel is supplied as a pass door as

The timber constructed panels have flush fitting protective aluminium edge profiles and the panel faces are available in a variety of finishes; painted, wood veneer, or a wide range of melamine or high pressure laminates.



Panel Thickness: 31 - 46dB, 65mm 48dB, 100mm



Max. panel width: Approx. 850mm



Max. panel height: 31 - 46dB, 4000mm 48dB, 3000mm 30/60 minutes, 3000mm



Weight per m²: 31dB: 19kg, 37dB: 20kg, 41dB: 28kg, 44dB: 30kg, 46dB: 39kg, 48dB: 47kg



Fire test: 30/60 minutes



Lab-tested acoustic insulation: Rw 31, 37, 41, 44, 46, 48dB







Centrefold



Endfold



Glazed folding walls

STYLEFOLD 900 - A glazed version of the STYLEFOLD 120 supplied either with single or double glazing. Integral Venetian blinds are optional with double glazed units. Standard manifestations are available or special designs can be provided.

STYLEFOLD 910 – generally as the STYLEFOLD 900 but with single glazing and an aluminium frame which can be polyester powder coated to any standard RAL colour. STYLEFOLD 910 is also available with two point suspension.



Panel Thickness: 900: 65mm 910: 60mm



Max. panel width: 900/910: 800mm



Max. panel height: 900: 2700mm 910: 4000mm



Weight per m²: Approx. 30kg, depending on type of glass



Fire test: None



Lab-tested acoustic insulation: max. approx. Rw 32dB depending on type of glass







Quality assurance

SWG quality assurance is your guarantee of a thoroughly tested performance product.

All processes – planning, production, assembly, internal and external procedures – are carefully defined and continually monitored.

SWG, in partnership with Style, offers extensive technical expertise in the design, production and fitting of the finished product; please feel free to draw upon this experience.

SWG quality ensures an excellent finished product and provides a comprehensive after sales service and support through Style's network of regional offices.

Product range:

- Moveable walls
- Folding walls
- Moveable glass walls
- Vertical rising walls (Electrically operated)

		120	900 / 910
Thickness of panel	>	31 - 46dB, 65mm 48dB, 100mm	900: 65mm 910: 60mm
Max. panel width	\longleftrightarrow	Approx. 850mm	Approx. 800mm
Max. panel height		4000mm (48dB - 3000mm)	900: 2700mm 910: 4000mm
Weight per m²		19 - 47kg	Approx. 30kg depending on type of glass
Fire test	21	30/60 minutes	None
Lab-tested acoustic insulation		Rw 31, 37, 41, 44, 46, 48dB	Approx. Rw 32dB depending on type of glass



