

SLIDEMASTER™

CANTILEVER SLIDING GATES



NSPlus

A

Heavy duty aluminium frame

B

Choice of infill

C

Totally enclosed track

Conforms to BS EN 12453



FEATURES

- Available in manual or automatic operation
- Clear drive through widths up to 20000mm
- Full range of panel infills
- Full range of RAL colours available

SUITABLE FOR

- Industrial and retail parks
- Data centres
- Airports and seaports
- MOD

CALL 01270 764751 OR VISIT WWW.CLD-FENCING.COM



DESCRIPTION

Ideal for everyday access needs, our base model SlideMaster™ cantilever sliding gates offer a unique blend of practicality and protection that's ideal for retail parks, industrial sites and other relatively low-level security locations.

With a heavy duty aluminium frame and your choice of infill – from standard vertical bar panels to any of our Mesh Panel products – SlideMaster™ gates not only offer great security, but they present a modern and professional entry and exit control.

You can choose from manual or automatic operation, and with double gate drive through widths of up to 20000mm, they allow access room for even the largest of vehicles. The track of the sliding gate is totally enclosed too, preventing damage from vandals.

Not only are they incredible cost effective, but SlideMaster™ gates also conform to the British Safety Standards (BS EN 12453) for power-operated industrial or commercial gates, so you have they added assurance that they're built with quality in mind.

FINISH

Aluminium or galvanised and polyester powder-coated. Available in the RAL range of colours.

DIMENSIONS

Gate width (single)	1200mm up to 10000mm
Gate width (double)	2400mm up to 20000mm
Operating speed	4 seconds per metre
Gate infill panel	CLD mesh options or vertical bar

Please seek technical advice on foundation details before specifying or installing this range.

All dimensions are nominal

SPECIFICATION CLAUSES

Please contact CLD on 01270 764751

