

ARSTYL® WALL TILES



Material

- Product name: ARSTYL® WALL TILES
- Constituent material: High-density, yellow, rigid polyurethane foam.
- Density: $\pm 300 \text{ kg/m}^3$
- Factory finish: Matt white acrylic primer to be painted.

Specific properties

- Visible surfaces:
The manufacturing technique guarantees a hard and smooth surface and the exact reproduction of the motif.
- Dimensions:
CORAL: $\varnothing 380\text{mm}$ (tolerance $\pm 5\text{mm}$)
WING: $250\text{mm} \times 175\text{mm}$ (tolerance $\pm 5\text{mm}$)
RAY: $550\text{mm} \times 320\text{mm}$ (tolerance $\pm 5\text{mm}$)



NMC sa
Gert-Noël-Strasse – B-4731 Eynatten
☎ +32 87 85 85 00 – 📠 +32 87 85 85 11
info@nmc.eu

walltiles.arstyl.com



ARSTYL[®] WALL TILES



Use

- Areas of application:
Decorative wall tiles for interior use.
- Fitting and storage conditions:
ARSTYL[®] WALL TILES must be stored flat in a dry place. The recommended temperature is +15 °C to +25°C with a relative humidity of 45% to 65%. To achieve optimum results, the products should be fitted under similar moisture and temperature conditions as present after the installation (indoor environment). Fitting on a wet backing surface (fresh plaster) and in forced drying conditions (heat gun, dehumidifier, exceptionally high temperature) are to be ruled out.

Backing

The following backing surfaces are suitable: indoor plastered or papered surfaces, coated plaster. Surfaces must be clean, dry, free from dust, degreased and flat; rough down if necessary. If the product is to be applied to particular backing surfaces, please consult our technical department.

Glue

- Assembly adhesive: ADEFIX[®] PLUS
- Optional: adhesive filler ADEFIX for grouting the ceiling and wall connection area when the wall tiles are installed on a whole wall
- Recommended room, adhesive and profile temperature:
+15°C to +25°C
- ADEFIX[®]: cleaning products before hardening: water
- ADEFIX[®] PLUS: cleaning products before hardening: turpentine substitute

ARSTYL® TILES



Surface work (painting)

The factory-primed ARSTYL® WALL TILES must be coated with a finishing paint. Water-based emulsion paints, acrylic or PU-based emulsion paints and alkyd resin paints are suitable. **It is always recommended to perform a test coat.** Lime paints, silicate paints, silicone resin colours and mixed products must not be used.

Special instructions

ARSTYL® WALL TILES are not designed to withstand loads.

With polyurethane materials there may be a slight dimensional change at increased temperature and humidity. A slightly visible joint can arise due to these material-specific properties at the panel joint area. **This is not a reason for complaint.**

Other technical data in accordance with DIN EN 15102+A1:2011 are given in the declaration of performance Nr. W1DECORP100 (www.nmc.eu/dop).