

PRODUCT DATA SHEET HPC 02

CI/SFB Vv4

January 2012

NU-GUARD® A.G. TACK PRIMER

DESCRIPTION:	Nu-Guard A.G. Tack Primer is a high performance water soluble, epoxy coating.
ADVANTAGES:	Provides first class adhesion to properly prepared surfaces
USES:	First coat of the Nu-Guard A.G. System. Developed to act as a tack primer over existing coatings and non porous substrates including glazed tiles.
COLOUR RANGE:	Off White
PACK SIZE:	Two component product, supplied in 5 litre units.
VOLUME SOLIDS:	40%
COVERAGE RATE:	8 m ² / Litre
DRYING TIME:	Touch :3 - 4 hours. Overcoat :8 hours.
PREPARATION:	Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded.
APPLICATION:	By brush/roller or spray. Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.
EQUIPMENT CARE:	All equipment should be cleaned with water immediately after use.
STORAGE:	Store away from direct sunlight and sources of heat. Protect from frost.
SHELF LIFE:	12 months (in original sealed container).
HEALTH & SAFETY:	Refer to health and safety sheets.



HYDRON
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494