

# PRODUCT DATA SHEET HPC 05

CI/SFB Vv4

January 2012

## NU-GUARD® A.G. HIGH SOLIDS FINISH

<b>DESCRIPTION:</b>	Nu-Guard A.G. is a siloxane-based coating with an excellent decorative appearance and outstanding resistance to solvents and chemicals, making it a first choice anti-graffiti coating for use on external surfaces.
<b>ADVANTAGES:</b>	Efficient graffiti removal with A.G.3 Graffiti Remover.
<b>USES:</b>	For use on a variety of substrates such as painted brickwork, render, concrete, metal and wood.
<b>COLOUR RANGE:</b>	Any BS4800 or RAL Shade
<b>PACK SIZE:</b>	Two component product, supplied in 1 and 5 litre units.
<b>VOLUME SOLIDS:</b>	90.00%
<b>COVERAGE RATE:</b>	16 m <sup>2</sup> / Litre
<b>DRYING TIME:</b>	Touch : .....2 hours. Overcoat : .....3 hours.
<b>PREPARATION:</b>	Ensure surfaces to be treated are clean, free from contamination and dry
<b>APPLICATION:</b>	By brush/roller or spray. Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.
<b>EQUIPMENT CARE:</b>	All equipment should be cleaned with Nu-Guard HS Thinners. Conventional thinners and brush cleaners are not effective.
<b>STORAGE:</b>	Store away from direct sunlight and sources of heat. Protect from frost.
<b>SHELF LIFE:</b>	12 months (in original sealed container).
<b>HEALTH &amp; SAFETY:</b>	Refer to health and safety sheets.



**HYDRON**  
Protective Coatings Ltd

Telephone: 01902 450950 Fax: 01902 451050



Certificate No. 20494