



TECHNICAL DATA SHEET – HPC 99 NU-FLAME FR COLOURCOAT

DESCRIPTION:

Nu-Flame FR Colour Coat is a flame retardant paint finish.
Also used as a basecoat for use prior to multi-coloured finishes.

ADVANTAGES:

Being a water soluble product this is safe for internal applications. **Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations.**

USES:

For use on walls and ceilings.
Intermediate coat of the Nu-Flame Multi-coloured System.

COLOUR RANGE:

In any BS400 or RAL Shade.

PACK SIZE:

Single component product, supplied in 5 & 10 litre units.

COVERAGE RATE:

14 m² per litre

VOLUME SOLIDS

40%

DRYING TIME:

Touch: 2 Hours
Overcoat: 4 Hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

By brush/roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

STORAGE:

Store away from direct sunlight and sources of heat.
Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS