



## Technical Data - tufftop jointing mortar

**tufftop** is a high performance, naturally pure hydraulically bonding mortar. It contains no polymer or resin additives and requires only the addition of water.

**tufftop** is a highly plastic, free flowing slurry grout which is easy to use and makes light work of surface cleaning.

**tufftop** penetrates even the most irregular joints and cavities and fills joint widths as small as 3 mm. Surplus applied water is displaced naturally and the mortar rapidly thickens before curing commences.

**tufftop** is shrinkage compensated, reducing the risks of failure associated with building permanent stress into bound paving, The inevitable result of excessive shrinkage, often caused by polymer and resin additives.

The elastic modulus of *tufftop* is optimised to provide the correct supporting stiffness whilst continually absorbing the thermal and dynamic stresses inherent in bound pavements.

**tufftop** complies with, or exceeds, the performance requirements of British Standards BS7533-7 & BS7533-12 Standards for Modular Paving.

Joint width	>3 mm
Typical water used	4-5 litres per 25 kg
Set time	24 hours
Working time	30 min at 20°C
Working temperature	2-30°C
Compressive strength (20°C)	14 days: ~30 N/mm² 28 days: ~45 N/mm²

Flexural strength	~7.5 N/mm²
Elastic modulus	(20,000 ± 4,000) N/ mm <sup>2</sup>
Adhesive bond	~1.5 N/mm²
Storage life	12 months from manufacture date
NBS sections	Q24 Q25
Compliance	BS 7533

**Storage life:** Twelve months in dry conditions (mortar can last longer if stored in moisture free conditions. Product remaining in a dry powder form continues to be fit for use)

**Ensure thorough mixing**: *tufftop* should be mixed in a plastic dustbin, or large mixing bucket using a powerful spiral mixing paddle, or more-effective electric twin paddle mixer. Alternatively use a forced action paddle mixer. In all cases, make sure the grout is mixed thoroughly with water until it becomes a smooth lump-free blend.

tufftop is supplied as a pre-mixed dry product packed in moisture resistant bags and is available in four standard colours: Natural Grey; Mid Grey; Dark Grey and Beige.





## Mid Grey Dark Grey Beige Natural Grey

Technical Data tufftop V3 Revised: 4 Feb 2020