











Product Code	Timber	Thickness	Width	Profile	Inserts	Section Drg.	Notes
HW19-90-S1	Bangkirai	19	90	Smooth	1		A very narrow board with just 1 insert. Suitable for domestic applications only.
HW19-90-S2	Bangkirai	19	90	Smooth	2		As above with 2 inserts for additional antislip coverage.
HW21-145-G2	Bangkirai	21	145	Grooved	2		A popular grooved hardwood option. Suitable for public access areas.
HW21-145-S2	Bangkirai	21	145	Smooth	2		As above with a smooth profile. A great looking product for commercial and domestic applications.
HW21-145-S3	Bankirai	21	145	Smooth	3		3 insert antislip coverage suitable for areas where pedestrian traffic is multi directional and not just perpendicular to the deckboards
HW-21-145-G4	Bangkirai	21	145	Grooved	4		4 insert antislip coverage suitable for very high traffic areas where pedestrian traffic is multi directional.

HW-28-145-G2	Bangkirai	28	145	Grooved	2		Our most popular 28mm thick hardwood option. 2 inserts meet the industry standard for general public access areas.
HW-28-145-S2	Bangkirai	28	145	Smooth	2		As above with a smooth profile. A great looking product for commercial and domestic applications.
HW28-145-S3	Bangkirai	28	145	Smooth	3		3 insert antislip coverage suitable for areas where pedestrian traffic is multi directional and not just perpendicular to the deckboards
HW-28-145-G4	Bangkirai	28	145	Grooved	4		4 insert antislip coverage suitable for very high traffic areas where pedestrian traffic is multi directional.

Note - Bangkirai is also known as Yellow Balau

The above profiles are standard and other species/profiles as detailed below are available on request.

Product Code	Timber	Thickness	Width	Profile	Inserts	Section Drg.	Notes
HW-Eo	European Oak	21-45	120-145	Grooved /Smooth	2-4	Various profiles	Yellowish brown with a medium to coarse texture. Strength Class D30/D40
HW-Ek	Ekki	34-75	120-145	Grooved /Smooth	2-4	Various profiles	A great marine timber available in large sections and a variety of profiles. Very durable. Strength Class D60
HW-Cu	Cumaru	28-34	120-145	Grooved /Smooth	2-4	Various profiles	Stable, strong and very durable. Russet red to deep brown colours. Strength Class D60
HW-Ga	Garapa	21	145	Grooved /Smooth	2-4	Various profiles	Golden to yellowish brown colour. Moderately rough and durable. Strength Class D40
HW-Ip	Ipe	21	145	Grooved /Smooth	2-4	Various profiles	Fine texture with great strength and very durable. Strength Class D60
HW-Ir	Iroko	34	145	Grooved /Smooth	2-4	Various profiles	Buttery yellow to brown-yellow in colour. Durable and stable. Strength Class D40
HW-Op	Opepe	28-45	145	Grooved /Smooth	2-4	Various profiles	Very resistant to decay and marine borers. Opepe is strong and very durable and makes an excellent flooring product. Strength Class D50
HW-Ma	Massaranduba	28-34	145	Grooved /Smooth	2-4	Various profiles	Rich in colour, dense, strong and durable-very durable. Limited specifications. Strength Class D60