

AllEdge Lawn Edging

Product Properties		ALP100M/300	ALP100M/450	ALP100M/600
Dimensions	Edging height	100mm	100mm	100mm
	Edging thickness (top bead)	5mm	5mm	5mm
	Edging length	2500mm	2500mm	2500mm
	Fixing stake length	300mm	450mm	600mm
Other	Available finishes	Mill Finish	Mill Finish	Mill Finish
	Material specification	6063A aluminium		
	Recycled content	Part recycled / 100% recyclable		

Product ALP100M shown below.



ALP100M
Mill Finish

Description

Flexible premium aluminium edge restraint for soft landscape surfaces available with various Flat Fixing Stake lengths. Powder coat finishes available on request.

Applications

To edge or demarcate lawn borders and other soft landscape applications. AllEdge uses Aluminium Alloy 6063A which is a high performance alloy with a high natural resistance to corrosive conditions in normal environments.

Installation Information¹

By mounting the edging using aluminium Flat Fixing Stakes and backfilling with landscape surfacing. Stake lengths of 300mm, 450mm and 600mm are available.

Storage & Handling

The product is securely packed in a single flute cardboard carton to ensure no movement of the product in transit and each carton is sealed with a fibre tape. Depending on the size / weight of the consignment this may be palletised.

Whilst there is no specific weight restrictions on what is or is not safe to lift in manual handling, an assessment of the health and safety risks should be undertaken and measures taken to reduce the risk of injury so far as reasonably practicable.

The following guidelines may be useful:

- Each person should be fully trained in manual handling techniques.
- The use of handling aids such as a trolley, folk-lift, pallet truck or conveyor should be used if moving large volumes of cartons.
- Break up large consignments into more manageable loads.
- Ensure that the product is stored at a reasonable height, so avoiding the lifting of cartons from floor level or above shoulder height.
- Reduce carrying distances of cartons.

Protective Equipment

We recommend that PPE (Personal Protective Equipment) is used when installing AllEdge:

- a) Good strong safety boots/shoes to protect the feet.
- b) Protective eyewear such as safety glasses.
- c) Strong gloves to protect the hands.
- d) If using loud cutting equipment then ear plugs or defenders should be worn.

First Aid

The Health and Safety Regulations 1981 require all construction sites to have the following:

- a) A first aid box with enough equipment to cope with the number of workers on site.
- b) An Appointed Person to take charge of first-aid arrangements. The Appointed Person looks after first aid equipment and facilities and calls the emergency services when required. Appointed Persons do not need first aid training.
- c) A First-Aider who has undertaken training and holds an HSE approved qualification to administer first-aid. This means that they must hold a valid certificate of competence in either:
 - First aid at work (FAW) issued by a training organisation approved by HSE
 - Emergency first aid at work (EFAW) issued by a training organisation approved by HSE
 - A recognised Awarding body of Ofqual/Scottish Qualifications Authority.
- d) The number of first-aiders will depend on the site.
- e) Information should be clearly displayed on site telling workers the name of the Appointed Person(s) or First Aider(s) and where to find them.

Fire Protection

AllEdge is made using Aluminium Alloy 6063A which does not burn and is not a fire hazard.

Stability

All building materials are eventually degraded by weathering, corrosion, rot and decay. Aluminium's natural ability to resist these influences better than many materials is one of its most widely appreciated features. Aluminium reacts with the oxygen in the air to form an extremely thin layer of

oxide; this layer is dense and provides excellent corrosion protection, and is self-repairing if damaged. In its unprotected 'Mill Finish' form aluminium is used very successfully for long-life everyday products making AllEdge exceptionally suitable for use as a commercial landscape edging system.

Environmental Issues

AllEdge is manufactured from recycled aluminium (80% recycled content minimum) and is 100% recyclable. As a result the whole life cost of aluminium edging is excellent as it is sold for recycling not paid disposal. The 20% virgin aluminium is blended with the recycled content to help achieve the proper chemical content for the alloy specification, which gives the specified mechanical properties for strength. Scrap aluminium is a valuable resource and can be recycled repeatedly.

There are plenty of raw materials for the production of aluminium. In a variety of forms, aluminium compounds make up a full 8% of the Earth's crust. Bauxite is the main starting point in the production of aluminium and given current rates of production there is enough bauxite to last another 200 to 400 years, this based upon no increases in the use of recycled aluminium and no further discoveries of bauxite. Furthermore the volume of aluminium being recycled is at a level where the requirement for virgin alumina is decreasing – further lessening the environmental impact.

Supporting Documents

More information on the AllEdge products can be found at www.kinley.co.uk in the Resource Centre. In particular, look for the CAD Drawings, Installation Guide (IG-AL-0316) and Brochure (BR-EB-0116).

1. The *Installation Information* given in this document is intended as a guide only. We recommend that professional opinions are obtained before work is commissioned. Kinley Systems Ltd accepts no responsibility for any damage or loss as a result of using the *Installation Information*. We will be happy to engage in any discussion with regard to specific project applications.