

ACADEMY

cycle shelters



▲ **ACADEMY Cycle Shelter**
galvanised finish with polycarbonate roof
installed at Foss Island Business Park, York
shown with five COLLEGE stainless steel cycle stands (see page 86-88)

Furnitubes range of Academy free-standing covered shelter units are an ideal way to encourage cycle use. The contemporary heavy duty steel frame is extremely strong and galvanised for long-term protection against the elements.

In a bid to reduce the amount of car journeys, staff and pupils are being encouraged to cycle to work and school. The provision of cycle stands and shelters reduces cyclists fear of theft or damage to their bikes, and protects bikes from the elements. Secure cycle parking at stations, interchanges and visitor attractions increases traffic flow and reduces congestion by promoting bicycle and rail travel through integrated transport.


The durable corrugated roof is available either galvanised or galvanised and plastisol colour coated. A 10mm dual-walled clear polycarbonate roof is also available as an attractive modern option.



▲ **ACADEMY Cycle Shelter**
supplied to King Egbert School, Sheffield
galvanised finish with polycarbonate roof
shown with seven COLLEGE stainless steel cycle stands (see page 86-88)

Shelters are supplied in kit form for assembly and installation on site. They are flanged for bolting down as necessary. The standard shelter can accommodate four College steel cycle stands, supplied separately (see pages 86-88). This will accommodate eight bicycles. Other combinations can be used.

Alternative shelter lengths, extension bays or bespoke designs are manufactured to order. Please contact a member of our Sales Team for more details.



▲ **ACADEMY Cycle Shelter**
plan view of cycle shelter
four cycle stands installed
accommodating eight bicycles



▲ **ACADEMY Cycle Shelter**
shown here at Silver End Road, Haynes
corrugated steel roof, galvanised finish
shown with four COLLEGE galvanised steel cycle stands (see pages 86-88)



ACADEMY

cycle shelter

ROOF PANELS SECURELY CLAMPED WITHIN RIB ASSEMBLY

SUBSTANTIAL Ø76 MILD STEEL GALVANISED FRAME CONSTRUCTION



detail
ROOF PURLIN SUPPORT BRACKET

EACH 300MM WIDE FOOT IS SUPPLIED WITH 8 HOLES FOR M16 BOLTS

▲ ACADEMY SHELTER
galvanised finish with polycarbonate roof

TECHNICAL

Standard shelters are designed to house eight standard bicycles.


Installation
Shelters are supplied in kit form for site assembly. Roofing needs to be drilled on-site. Full instructions are provided.

We recommend that each foot is bolted down into a minimum concrete foundation size of 400 x 400 x 400mm.

Powder Coating
The Academy Cycle Shelter can be powder coated, providing a hardwearing, weatherproof surface. Large range of BS/RAL colours are available. For further information on paint finishes see pages 337-339.

Product Codes are in **bold type**. Dimensions are in mm, are approximate and do not form any part of the contract.

We reserve the right to change the design and specification on any item offered and, where possible, notification will be made.



ACADEMY CYCLE SHELTER RANGE

ACA 800 F

3450mm Freestanding Bolt-Down Shelter
Galvanised Steel Frame Finish
Galvanised Steel Corrugated Roof

OPTIONS

Powder Coated finish

ACA 800 FP

3450mm Freestanding Bolt-Down Shelter
Galvanised Steel Frame Finish
Galvanised Steel Corrugated Roof, Plastisol Finish

OPTIONS

Powder Coated Finish
4000mm overall length

ACA 800 TP

3450mm Freestanding Bolt-Down Shelter
Galvanised Steel Frame Finish
10mm Twin Clear Polycarbonate Glazed Roof

OPTIONS

Powder Coated Finish
4000mm overall length

