


TIMBER BOLLARDS - ASHDOWN RANGE

Premium circular bollards

Ashdown is a premium range of circular bollards with a high quality machined finish, including a domed top to aid water run-off. The range is particularly suited therefore to urban applications where pedestrians may come into close contact with the bollards, although they are also popular in roadside verge situations.


Opepe - classified as Very Durable hardwood with good fire resistance - is the standard material for the Ashdown range, finished with a coat of woodstain to provide a soft sheen finish and extend the rich colouration as the timber weathers over time.

Ø125-225



500-1000 a/g

250-500 b/g



Standard grooved neck position

Variations to standard dimensions and grooved neck positions can be supplied on request

Refer to table for standard section and above / below ground dimension combinations

ASHDOWN

Above ground:	500mm	600mm	800mm	1000mm
Below ground:	250mm	300mm	400mm	500mm
Ø125mm	ARP 125/750	ARP 125/900	ARP 125/1200	ARP 125/1500
Ø150mm	ARP 150/750	ARP 150/900	ARP 150/1200	ARP 150/1500
Ø175mm	ARP 175/750	ARP 175/900	ARP 175/1200	ARP 175/1500
Ø200mm	ARP 200/750	ARP 200/900	ARP 200/1200	ARP 200/1500
Ø225mm	ARP 225/750	ARP 225/900	ARP 225/1200	ARP 225/1500

STANDARD SPECIFICATION:

Opepe hardwood with Sadolin Woodstain finish, colour 'Mais'
(Material is subject to availability - alternatives may be offered including Wallebe and Greenheart)

OPTIONS:

- With grooves and optional reflective tape
- Pre-drilled to accept circular steel rails
- Pre-fitted eyebolts for chainlink connection
- Reflective plates, discs or D.f.T. sign plates (only bollards with grooves)
- Removable bollard with galvanised mild steel or stainless steel socket

