



Tried, Tested, Trusted

POLYSoundBlok®

REFLECTIVE

Class	Acoustic Performance	Design Life	Replacement Design Life Based on 120 years.	
B3 A0	DL _R 25 dB Dl _α 0 dB(A)	40 years - Panels 60 Years Posts	2	1
Foundation Type		Fixing Method / Post Type	Fixings	Maintenance
1) Shallow concrete pad footing set a 3.0 or 5.0m centres. 2) Augered foundations set at 3.0m or 450m centres.		1) Galvanised steel or PPC posts with baseplates fixed to concrete pad footings using chemfix resin anchors/studs. 2) Steel RSJ posts set into augered foundations using ST5 concrete.	Stainless Steel	Zero Maintenance. Year inspection required.



GRAMM BARRIER SYSTEMS LTD
NOISE BARRIER & FENCING SPECIALIST

Images and photos are property of Gramm Barrier Systems and must not be duplicated or disrupted without permission.



POLYSoundBlok®
REFLECTIVE



GRAMM BARRIER SYSTEMS LTD
NOISE BARRIER & FENCING SPECIALIST

Images and photos are property of Gramm Barrier Systems and must not be duplicated or disrupted without permission.



POLYSoundBlok®

REFLECTIVE

