



Althon 400mm Resilient Flap Valve Mounting Specification Information

The O ring item 7 is for mounting the flap valve onto a pipe flange or high quality flat surface and is supplied as part of the fixing kit which needs to be ordered separately.
For standard wall mounting the flap valve should be grouted in the normal way.

400MM RESILIENT FLAP VALVE				
ITEM	QTY	PART NUMBER	DESCRIPTION	MATERIAL
1	1	400RESDOOR	400mm Door	Ductile iron casting
2	1	400RESFACE	400mm Resilient Face	Resilient epoxy material
3	2	LINKR1	400mm Hinge Link	Ductile iron casting
4	1	400FRAMERESASME	400mm Frame	Ductile iron casting
5	4	16MMPIN	400mm Hinge Pin	Stainless steel - grade 316
6	8	M16STAR	16mm Star Washer	Stainless steel - grade 316
7	1	440X12ORING	440x12 O Ring	Neoprene foam

ADDRESS: ALTHON LIMITED
VULCAN ROAD SOUTH
NORWICH
NR6 6AF

TEL: 01603 488700
FAX: 01603 488598
EMAIL: sales@althon.co.uk
WEBSITE: www.althon.co.uk

DRAWING TITLE:

**400MM DUCTILE
IRON FLAP VALVE**

SCALE: NTS PAPER: A1 DATE: 02 - 09 - 15

DRAWING No: 400FV