ANTI-TRAP BOW TOP





Anti-Trap Bow Top is designed to provide permanent protection for a variety of applications including schools, parks or play areas.

It features our welded tubular pale-through-rail design to provide a strong structure without visible joints and vandal proof connectors. A key feature of the design is the wider gap between each hoop above the top rail, which prevents children from getting their heads, necks or limbs stuck between the pales. The design fully conforms to play fence standards in BS EN 1176.

- 19mm pales with domed top caps
- 2737mm wide panels
- Posts 60.3mm
- Panels can be manufactured to accommodate sloping ground
- 25-year service life guarantee

APPLICATIONS

- ✓ Schools
- ✓ Parks
- ✓ Play areas

PANELS

Two horizontal rails 50 x 25mm with vertical round hollow section 19mm pales are passed through the top and bottom rail welded into position.

Every other bow with a pale is replaced with a domed plastic insert, creating a larger gap above the top of the rail, whilst keeping the gap between the

paling inside the top and bottom rail under 100mm.

Post to panel fixings

GATE OPTIONS

- Self closing operation for gates
- Slide latch





| неіднт (мм) | POST CENTRES (MM) | POST DIMENSIONS (MM) | OVERALL POST LENGTH (MM) |
|-------------|-------------------|----------------------|--------------------------|
| 1000 | 2775 | 60.3 Ø | 1500 |
| 1200 | 2775 | 60.3 Ø | 1800 |
| 1500 | 2775 | 60.3 Ø | 2100 |
| 1800 | 2775 | 60.3 Ø | 2500 |

POST OPTIONS

- Overlength set in concrete as standard
- Baseplated to bolt down onto concrete
- Cranked to suit wall mounting

FINISHES

- Hot dip galvanised to BS EN ISO 1461 as standard
- Hot dip galvanised and powder coated to BS EN 13438
- Marine coat for installations within 500m of salt water or an estuary

STANDARD COLOURS

- Black RAL 9005
- Green RAL 6005
- Other colours are available on request

