

# TRI-GUARD® SLIDING GATES



Tri-Guard® swing and sliding gates are a perfect match to Tri-Guard® fencing sharing the unique triple pale design feature and fully welded pale-through-rail construction.

- Ideal for applications where space is limited or ground obstacles need to be spanned
- Pales Ø 19mm
- Horizontal rails for all gates are 60x40mm. Hanging and shutting stiles are rectangular hollow section 60x60mm
- Single or double leaf options available
- Cantilever or tracked options available
- Manual or automated operation
- Available in a range of standard widths to span up to 30m and in heights up to 3m
- Effective operation in applications subject to high wind loading

## FINISHES

- Hot dip galvanised to BS EN ISO 1461 as standard
- Hot dip galvanised and powder coated to BS EN 13438
- Marine coat for installations within 500m of salt water or an estuary

## POST OPTIONS

- Overlength set in concrete as standard
- Baseplated to bolt down onto concrete



- Materials: Portals: 80 x 80 Sq, Stiles: 60 x 60 Sq, cantilever running tube:  $\varnothing$ 178, Tracked running tube: 200 x 100
- Automated: Class 1 hold to open / close or Full Class 3 operation to suit current CE safety regulations including flashing light, photocells & safety edges. Motors to suit various gate sizes and open/close cycles.

Height (mm)	Post Centres (mm)	Post Dimensions (mm)	Overall Post Length (mm)
2200	3010	80 x 60	3000
2500	3010	80 x 60	3000

## CONTACT

T: 0800 41 43 43

E: [security@jacksons-fencing.co.uk](mailto:security@jacksons-fencing.co.uk)

W: [www.jacksons-fencing.co.uk](http://www.jacksons-fencing.co.uk)