

HARRIER PAS 68 STATIC BOLLARDS

The Harrier PAS 68 Static Bollard range are designed to protect localised areas within a perimeter with an unobstructive barrier capable of arresting or completely halting the progress of a hostile vehicle. Used in series, the bollards are equally effective in the protection of buildings and for use in support of traffic calming measures where a reduction in vehicle approach speeds and/or direction is required.

The bollards are manufactured in our workshops using heavy gauge steel which is fully hot-dip galvanised to provide lasting protection and may be additionally colour coated or cloaked with a decorative stainless steel cover.

- ▶ Stand-alone system for outer boundary protection or target hardening within a perimeter



| | TUBE DIAMETER (MM) | APPROVALS |
|-----------|--------------------|--------------------------|
| Harrier 1 | 219 | 7500(N2)/48/90:0/0 |
| Harrier 2 | 273 | 7500(N2)/64/90:3.3/0 |
| Harrier 3 | 219 | 7500(N3)/64/90:4.0/16.7 |
| Harrier 4 | 273 | 7500(N3)/80/90:10.6/11.1 |

APPLICATIONS

- ✓ High risk
- ✓ Data centres
- ✓ Power stations
- ✓ Oil and Energy
- ✓ Government

APPROVALS



FINISHES

- Heavily galvanised to BS EN 1461 as standard
- Polyester Powder Coated
- Marine coat for installations within 500m of salt water or estuary

STANDARD COLOURS

- Black RAL 9005
- Green RAL 6005
- Other colours are available on request