

12K ENVIROFENCE®

**Jacksons
Fencing**



A lighter 20mm thick board than our other Jakoustic® barriers, maintaining the same 125mm cover face. Planed Tongue and Grooved boards with small chamfers which form a "V" join between boards. Suitable for installation where the required noise reduction is lower than that which would be provided by the standard Jakoustic® noise barrier - or where a superficial mass of 10, 11 or 12kg/m² is specified.

- Lighter weight with 20mm x 125mm nominal with a planed finish throughout x 4.8m boards
- Attractive timber construction
- Achieves the planning / architects' minimum acoustic specification of 10 - 12kg per sqm
- Capping rail 34mm x 145mm x 4.8m (planed)
- Counter rail size 34mm x 70mm x 2.4m (planed)
- Only available in reflective
- 25-year Jakcure® guarantee

APPLICATIONS

- ✓ Schools
- ✓ Parks
- ✓ Low - Medium risk
- ✓ Housing developments

GATES

Matching gates available



- ▶ Heights available with timber tuning fork posts* (for general applications away from hills and coasts).
- ▶ For barrier heights 2.1m - 3.0m the timber posts are reinforced with a steel spur post, powder coated black.

HEIGHT (MM)	POST CENTRES (MM)	SPUR POST (MM)	POST LENGTH (MM)
2000	2410	N/A	2900
2500	2410	2000	3400
3000	2410	2500	3900

*For taller heights, see Jakoustic® Commercial and Highway, which is constructed on galvanised steel I beam posts.

POST OPTIONS

- Timber tuning fork posts overlength set in concrete as standard

FINISHES

- Jakcure® treated timber as standard