



Broadrib Tile

Generated on 09.10.2017

Detailed description

Broadrib Tile is an 8 mm thick bitumen backed 500 x 500 mm tile manufactured with 80% polypropylene, 15% polyamide and 5% recycled polyester. It is designed for use in most building situations, including computer rooms.

Laying:

- Recommended carpet layout - the method of installation should conform to BS5325.
- For details of subfloor preparation and a full guide to installation visit manufacturer's website.
- Before laying Broadrib tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels.
- Broadrib tiles should be laid rotationally, alternating the direction of the tiles through 90°.

Adhesive Guide:

For tiles use F.Ball F41 or Bostick Laybond Carpet Tile Tackifier.

Product guidance - As Standard

Type:

Fibre bonded thick rib carpet tile.

Size:

500 x 500 mm.

Thickness:

8 mm.

Weight:

4020 g/m².

Colour Fastness:

- Light (BS EN ISO 105:B02) >6.
- Wet Rubbing (BS EN ISO 105:B01) 5.
- Dry Rubbing (BS EN ISO 105:X12) 5.

Options

Colour:

Available in 24 standard colourways.

Heckmondwike FB



Heckmondwike FB

Wellington Mills
Liversedge
West Yorkshire
WF15 7FH

Tel: +44 (0)1924 406161

www.heckmondwike-fb.co.uk
sales@heckmondwike-fb.co.uk



Product specification

Manufacturer

- Name: Heckmondwike FB
- Web: www.heckmondwike-fb.co.uk
- Email: sales@heckmondwike-fb.co.uk
- Tel: +44 (0)1924 406161
- Fax: +44 (0)800 136769
- Address: Wellington Mills, Liversedge, West Yorkshire WF15 7FH

Product reference Broadrib Tile

Colour

Acorn
Amethyst
Anthracite
Astra Blue
Azure
Blue
Blue Moon
Blueberry
Claret
Cobalt
Emerald
Flint
Graphite
Indigo
Kingston Grey
Magenta
Onyx
Pacific Blue
Pale Olive
Purple
Pebble
Steel
Violet
Willow