

Home of Random Biological Filter Media

Page 1 of 2

Biomarble



Technical Information

MaterialPolypropylene*Specific Gravity0.97Dimensions46 x 36 mmSurface Area310 m² / m³Voidage90%Weight (dry)76 kg / m³Weight(operational)up to 583 kg / m³Consolidation5 - 10%Flow DirectionNon specific		
Dimensions46 x 36 mmSurface Area310 m² / m³Voidage90%Weight (dry)76 kg / m³Weight(operational)up to 583 kg / m³Consolidation5 - 10%	Material	Polypropylene*
Surface Area310 m² / m³Voidage90%Weight (dry)76 kg / m³Weight(operational)up to 583 kg / m³Consolidation5 - 10%	Specific Gravity	0.97
Voidage90%Weight (dry)76 kg / m³Weight(operational)up to 583 kg / m³Consolidation5 - 10%	Dimensions	46 x 36 mm
Weight (dry)76 kg / m³Weight(operational)up to 583 kg / m³Consolidation5 - 10%	Surface Area	310 m² / m³
Weight (operational) up to 583 kg / m ³ Consolidation 5 - 10%	Voidage	90%
(operational) up to 583 kg / m ³ Consolidation 5 - 10%	Weight (dry)	76 kg / m³
Consolidation 5 - 10%	Weight	
	(operational)	up to 583 kg / m ³
Flow Direction Non specific	Consolidation	5 - 10%
	Flow Direction	Non specific

*Recycled polypropylene

With a spherical design and surface area of 310m²/m³, Biomarble has the highest surface area of the three spherical designs in the Biomedia filter range.

With purpose-designed features Biomarble, in the Warden Biomedia filter range, is an excellent alternative to traditional mineral-based media and is ideal for improved performance in new wastewater treatment plants.

Biological filter media of the relevant dimensions can replace all or part of the mineral-based media to improve system efficiency where it has become impaired by overloading. The surface texture of Warden Biomedia enables biomass or bacteria to adhere more effectively to reduce the loss of media due to installation procedures.

Modern plastic filter media eliminate problems relating to clogging and puddling associated with gravel, slag and clinker filter beds. Former biofilters using stones, slag or coke can easily be clogged after some time of operation. Modern technical solutions allow very high reduction of biogenic compounds. Reactivation and modernization of old type biofilter treatment plants is much cheaper than reconstruction of the treatment plants.

Features

Warden's biological filter media are feasible for both industrial and municipal wastewater and are used for organic removal, nitrification and denitrification.

- · Low weight
- Large active surface area
- Compact
- · Easy upgrade of existing plants
- · Durable, long-life
- · Minimal clogging
- · Random filter media
- · High BOD5 reduction (up to 90%) and nitrification
- · Low capital, low installation, operating and maintenance costs
- · Corrosion resistant components

Suitable Applications

Biomarble caters for a wide range of biological wastewater treatment plants of different sizes serving

- · New housing developments
- · Commercial premises



Page 2 of 2

Home of Random Biological Filter Media

Biomarble

- Single dwellings
- · Small or large SAF units
- · Municipal wastewater treatment plant
- · Industrial wastewater treatment plant

For random biological filter media - from the largest municipal sewage treatment plant down to a garden fishpond - Warden Biomedia has you covered, with the experience and knowledge to assist you in selecting of the right filter media for your application. Contact us today to see how we can work for you.



