



## OPTICAL GAS IMAGING FOR CONTINUOUS LEAK MONITORING

# FLIR GF77a



FLIR brings its low-cost optical gas imaging solution to the industrial automation market with the GF77a: an uncooled thermal camera that's spectrally filtered for methane and other industrial gases. This camera provides oil and gas facilities, gas transportation terminals, and power generation plants with continuous, autonomous leak detection. While it's small and lightweight, the FLIR GF77a is packed with FLIR-patented features such as High Sensitivity Mode (HSM), as well as open architecture allowing third-party analytic solution integration for visual confirmation of leak. The FLIR GF77a can help companies throughout the oil and gas industry better maintain valuable capital equipment, avoid product loss, meet emissions reduction metrics, and ensure safer work practices.

[www.flir.com/gf77a](http://www.flir.com/gf77a)



### DEPENDABLE, AFFORDABLE FIXED OGI SOLUTION

Uncooled camera offers many FLIR industry-leading features for continuous monitoring applications

- Increase leak detectability by activating FLIR-patented High Sensitivity Mode (HSM)
- Remote motorized focus ensures a crisp image and measurement accuracy for objects at different distances
- See more with dual-streaming capabilities from thermal plus built-in digital cameras
- Simple third-party integration thanks to open architecture



### DESIGNED TO VISUALIZE INDUSTRIAL GASES

Spectrally-filtered to detect gases, improving worker safety and leak location identification

- Continuously monitor for methane emissions so you can begin repairs immediately
- Visualize gases in specified spectrum while also reducing false negatives of gases that absorb in another wavelength
- Temperature-calibrated for added use in thermography, fire detection, and worker safety
- Install multiple units across a facility to maximize leak detection with fewer in-person inspections



### ADVANCED FEATURES FOR UNMATCHED CONNECTIVITY

State-of-the-art technology allows simple integration to meet existing industrial needs

- Connects to a network for continuous, autonomous leak detection
- RTSP and GigE compliant for flexibility to meet many industrial communication needs
- ONVIF compliant to ease integration with standard security and NVR solutions
- Compressed radiometric image streaming saves network bandwidth and allow multiple outputs simultaneously

## SPECIFICATIONS

Image and Optical Data		
IR resolution	320 × 240 (76,800) pixels	
Thermal resolution/NETD	<25 mk at 30°C (86°F)	
Gas sensitivity/NECL	CH <sub>4</sub> (<100 ppm × m), N <sub>2</sub> O (<75 ppm × m), C <sub>2</sub> H <sub>6</sub> (<400 ppm × m); ΔT = 10°C, distance = 1 m	
Spatial resolution (IFOV)	1.4 mrad/pixel	
Image frequency	30 Hz	
Field of view (FOV)	25° lens: 25° × 19°, 6° lens: 6.4° × 4.9°	
Focal length	25° lens: 18 mm, 6° lens: 74 mm	
Minimum focus distance	0.3 m (0.98 ft) for 25° lens; 5 m (16.4 ft) for 6° lens	
Focus	One-shot contrast, motorized, manual	
Detector data		
Focal plane array/spectral range	Uncooled microbolometer / 7 - 8.5 μm	
Detector pitch	25 μm	
Visual imaging and optical data (optional)		
Visual resolution	2592 × 1944 pixels	
Visual focus and FOV	Fixed, 67.2° diagonal	
Video lamp	Built-in LED light	
Measurement		
Object temperature range	-20°C to 70°C (-4°F to 158°F)	
Accuracy	±5°C (±9°F) for ambient temperature 15°C to 35°C (59°F to 95°F) and object temperature above 0°C (32°F)	
Measurement corrections	Global object parameters	
Correction options	Atmospheric, optics transmission, emissivity, reflected apparent temperature, external optics/window	
Ethernet		
Web interface	Yes	
Ethernet connector type	M12 8-pin X-coded, female	
Ethernet communication	GigE Vision ver. 1.2, Client API GenICam compliant, TCP/IP socket-based FLIR proprietary	
Ethernet image streaming	Yes	
Ethernet power	Power over Ethernet, PoE IEEE 802.3af class 3	
Ethernet protocols	IEEE 1588, ONVIF-S, SNMP, TCP, UDP, SNTP, RTSP, RTP, HTTP, ICMP, IGMP, sftp (server), FTP (client) SMTP, DHCP, MDNS (Bonjour), uPnP	
Image streaming		
	RTSP Protocol	GVSP (GigE Vision)
Unicast	Yes	Yes
Multicast	Yes	Yes
Multiple image streams	Yes (for ONVIF, 1 stream only)	No

Video streaming	RTSP Protocol	GVSP (GigE Vision)
<b>Image source 0</b>	Visual, IR, MSX®, 640 × 480 pixels	
Contrast enhancement	FSX®, histogram equalization (IR only)	
Overlay	With, without	
Encoding	H.264 / MPEG4 / MJPEG	Uncompressed
<b>Image source 1</b>	Visual, 1280 × 960 pixels	
Overlay	No	
Encoding	H.264 / MPEG4 / MJPEG	-
Radiometric streaming	RTSP Protocol	GVSP (GigE Vision)
<b>Image source</b>	IR, 320 × 240 pixels	
Pixel format	MONO 16	
Encoding	Compressed JPEG-LS, FLIR radiometric	Uncompressed, signal linear, temperature linear, FLIR radiometric
Digital input/output		
Connector type	M12 Male 12-pin A-coded (shared with ext. power)	
Digital input	2× opto-isolated, Vin (low) = 0–1.5 V, Vin (high) = 3–25V	
Digital output	3× opto-isolated, 0–48 VDC, max. 350 mA (derated to 200 mA at 60°C). Solid-state opto relay, 1× dedicated as fault output (NC)	
Power system		
Connector type	M12 Male 12-pin A-coded (shared with Digital I/O)	
General	PoE or External	
Power consumption	6.8 W at 24 V DC typical 7.0 W at 48 V DC typical 7.3 W at 48 V PoE typical	
External voltage	Allowed range = 18-56 VDC, 8 W max	
	Pan and Tilt (Optional)	Wi-Fi
Connector	M8 A-coded, male	Female RP-SMA
Serial communication	RS232 and RS485 exclusively	-
Standard	Pelco D	IEEE802.11a/b/g/n
Connection type	-	Peer to peer (ad hoc) or infrastructure (network)
Physical data		
Encapsulation	IP 54 (IEC 60529) IP66 with accessory	
Weight	0.82 kg (1.8 lbs)	
Size (L × W × H)	123 × 77 × 77 mm (4.84 × 3.03 × 3.03 in)	

For a complete list of specifications, go to [www.flir.com/gf77a](http://www.flir.com/gf77a)

**CORPORATE HEADQUARTERS**  
FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
USA  
PH: +1 866.477.3687

**LATIN AMERICA**  
FLIR Systems Brasil  
Av. Antonio Bardella, 320  
Sorocaba, SP 18085-852  
Brasil  
PH: +55 15 3238 8070

**EUROPE**  
FLIR Commercial Systems  
Luxemburgstraat 2  
2321 Meer  
Belgium  
PH: +32 3 665 51 00

**ASIA**  
FLIR Systems Co. Ltd.  
Room 1613 – 16, Tower 2  
Grand Central Plaza,  
No. 138 Shatin Rural Committee Road  
Shatin, New Territories  
Hong Kong  
PH: +852 2792 8955

[www.flir.com](http://www.flir.com)  
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2020 FLIR Systems, Inc. All rights reserved. 01/03/20

19-2259-INS-OGI - A4



The World's Sixth Sense®