



Timber Coaters Ltd

Factory Finished Timber Coatings

0151 230 1025; 07778 461644; Fax 0151 342 5205; email: timbercoaters@aol.com; www.timbercoaters.com

Unit 4 Wrynose Road
Old Hall Industrial Estate
Bromborough, Wirral
CH62 3QD

The attached goods have been Fire Treated with HR Prof Fire Retardant and the following notes should be understood:

CERTIFICATION: BS EN 13823 & BS EN 11925-2 SBI Euro class B-s1-d0.

(Equivalent to UK Class O BS 476: Part 6 & BS 476: Part 7)

NT 053 & NT 054 Accelerated weathering of Fire-Retardant treated wood for fire testing.

Euro-class C (Equivalent to UK Class 1 & 2) for plywood.

Drying Times: Maximum fire retarding capabilities achieved after 7 days.

Drying times are dependent upon absorption of substrate and drying conditions. At low temperatures and / or conditions of high relative humidity, drying times will be extended.

These goods were treated on 24/06/19, and must be kept in clean, covered dry conditions for a period of at least 7 days from this date. Failure to do so will reduce the effectiveness of the product, and no responsibility for its transportation, storage, maintenance or use will be taken after it has left our premises.

Health & Safety – During application avoid contact with open wounds, eyes and mouth. In the event of accidental contact wash the affected area immediately with clean water. Safety goggles and gloves should be worn when handling and applying the material.

Water based product, which does not present a health hazard under normal industrial use.

Maintenance: No maintenance is required once HR-Prof has been absorbed into the surface of the substrate and dried.

Signed:  _____

Ref: Sample Co Ltd
Timber Spec as follows:

Print: Graeme Thomas