

Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 03704 11 22 33 https://www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943

E: services.advisory@marshalls.co.uk

Conservation Textured Step 350 x 150 x 1000

Date Created: 07/02/19





Conservation Textured Step -Silver Grey

Marshalls' Single Solid Concrete Step Units are manufactured in concrete with lightly textured granite aggregates, making them a durable and attractive option for any urban environment. The Single Solid Concrete Step Units come equipped with 55mm wide visibility strips that are set 35mm from the edge of the kerb both horizontally and vertically. These standard strip colours meet the BS 8300 light reflectance values (LRV) standards. Available in 2 colours, the product serves as a versatile complementary step unit to use with numerous paving and block paving ranges, including La Linia, Mistral and Conservation. The product is also offered in 2 different plan sizes. Single Solid Concrete Step Unit products are also DDA compliant and manufactured to Marshalls' high standards.

DESCRIPTION	
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1339 : 2003
NBS Specification	Q25 31























Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 03704 11 22 33 https://www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943

E: services.advisory@marshalls.co.uk

Date Created: 07/02/19

Conservation Textured Step 350 x 150 x 1000

PHYSICAL PROPERTIES Work Dimensions (mm) 348 x 148 x 998 Nominal Dimensions (mm) 350 x 150 x 1000 Class 2 tolerances to all dimensions as Tolerances on Work Dimensions (mm) standard Length ±2mm, width ±2mm, thickness ±3mm Durability (Freeze-thaw) ≤ 1.0 kg/m² as a mean with no individual value > 1.5 kg/m² Material Density 2300 kg/m³ (typically) Slip/Skid Resistance Mean polished skid resistance value (polished) (PSRV): > 45 Slip/Skid Resistance Mean unpolished skid resistance value (unpolished) (USRV): > 45.

FURTHER INFORMATION

Contact Us

For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233



Carbon Footprint Available on Request



















