



The VELOPA Bilton Cycle Stand

The tubular cycle stand, a familiar sight throughout the UK, allows the frame of the bicycle to be secured by the users own security lock. Suitable for securing two bicycles.

The practical and durable nature of the VELOPA Bilton tubular cycle stand ensures it has been consistently favoured by both specifiers and users since it's introduction in the 2000's.

Shown are the galvanised and galvanised & coated flanged versions of the Bilton Cycle Stand.

Options

Order Code	Description	Weight
138515105	Ragged (Galvanised)	11.0kg
138515101	Flanged (Galvanised)	11.0kg
138515110	Ragged (Galvanised & Coated; specify BS/RAL colour)	11.0kg
138515102	Flanged (Galvanised & Coated; specify BS/RAL colour)	11.0kg
138515114	Ragged (Stainless)	11.0kg
138515104	Flanged (Stainless)	11.0kg
Accessories & installation parts		
138100994	12mm Expanding Bolt (Flanged only; 6 required per stand)	

Product details

750mm x 750mm (Length x Height)
48mm outside diameter tube.

Installation & use

Flanged versions require bolting to established concrete of at least 300mm cubed per leg.
Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 450mm (length x width x depth)
Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction.
This product is guaranteed for 12 months (if installed and used correctly).



www.velopa.co.uk
+44 (0)1788 550556

AUTOPA LTD. (03428445)
QMS 9001 (FM31071), EMS 14001 (EMS50316) & OHSAS 18001 (OHS552103).

