



The VELOPA Type C Cycle Rack

The VELOPA Type C Cycle Rack is a floor mounted cycle rack based upon the Model R Holder. The Type C offers a high cycle parking density, with cycle stands on both sides. The double sided holders combined ensure that cycles are parked 305mm apart (typical parking distance for a Sheffield Cycle Stand is 500mm).

The practical and durable nature of the VELOPA Type C Cycle Rack ensures that the rack is suitable for all environments where high density, double sided cycle parking is required.

Options

| Order Code | Description | Weight |
|-------------|---|--------|
| 138 200 231 | Type C Cycle Rack for 2 Bicycles (Ragged) | 8.0kg |
| 138 200 232 | Type C Cycle Rack for 2 Bicycles (Flanged) | 8.0kg |
| 138 200 431 | Type C Cycle Rack for 4 Bicycles (Ragged) | 16.0kg |
| 138 200 432 | Type C Cycle Rack for 4 Bicycles (Flanged) | 16.0kg |
| 138 200 631 | Type C Cycle Rack for 6 Bicycles (Ragged) | 24.0kg |
| 138 200 632 | Type C Cycle Rack for 6 Bicycles (Flanged) | 24.0kg |
| 138 200 031 | Type C Cycle Rack for 10 Bicycles (Ragged) | 40.0kg |
| 138 200 032 | Type C Cycle Rack for 10 Bicycles (Flanged) | 40.0kg |

(Please Note. The above is only a selection of the available sizes.)

Accessories & installation parts

| | |
|-------------|--|
| 138 100 994 | 12mm Expanding Bolt (Each. For numbers required please ask.) |
|-------------|--|

Product details

465mm x 380mm (Height x Depth)
Length dependent on number of Holders; 305mm between centres.
Mild Steel, Galvanised tube, bar and plate.

Installation & use

Flanged version of the Cycle Rack must be bolted to a suitable concrete surface.
Ragged version requires casting into concreted hole, not less than 300mm x 300mm x 350mm
Depending on Cycle Rack size specified some on-site assembly may be required.
This product is guaranteed for 12 months *(if installed and used correctly)*.



www.velopa.co.uk
+44 (0)1788 550556

AUTOPA LTD. (03428445)
QMS 9001 (FM31071), EMS 14001 (EMS50316) & OHSAS 18001 (OHS552103).

