







The AUTOPA Domed Top Bollard

The AUTOPA Domed Top Bollard combines mild steel tube with a high grade, impact resistant, malleable cast iron cap. The Domed Top Bollard is an elegantly simple bollard, ideal for providing protection against unauthorised parking or access. The Domed Top Bollard is ideal for use around pedestrian precincts, pavements, play and parking areas, as part of traffic calming measures, pedestrianisation schemes and as a deterrent to ram-raiders.

The Domed Top Bollard is available in galvanised and galvanised & coated finishes. It is also available Ragged for casting in to concrete, Flanged for bolting down or in Removable versions.

The AUTOPA Domed Top Bollard is shown in 76mm galvanised tube.

Pro	odu	ct	Ran	ge

Order Code	Description	Weight
138 121 135	60mm (Removable)	16.0kg
138 121 265	76mm (Removable)	18.0kg
138 121 272	90mm (Removable)	19.0kg
138 121 342	101mm (Removable)	19.5kg
138 121 440	114mm (Removable)	20.0kg
	Accessories and installation parts	
138 150 206	Additional Ground Socket	
138 100 906	40mm Brass Padlock with 2 Keys (Random Key)	
138 100 907	40mm Brass Padlock with 2 Keys (Identical Key)	

Product details

1,000mm Tall. 267mm below ground depth. Galvanised steel finish.

Installation & use

Removable bollards require an excavated hole of at least 300mm square and 400mm deep for the socket. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them.

This product is guaranteed for 12 months (if installed and used correctly).



