



GFC 1700 Ornamental Bollard

The GFC 1700 is an attractive and functional ornamental bollard. The body of the bollard is manufactured from mild steel and galvanised for longevity and features a cast domed cap. Two rings of cast iron are welded onto the steel body to complete the design.

The bollard is available in a galvanised and a galvanised and coated finish (RAL/BS numbers must be specified at time of order). Supplied ragged as standard, flanged and removable versions are also available.

Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

Product Range

Order Code	Description	Weight
138 120 251	Ragged (Galvanised)	15.4kg
138 120 252	Ragged (Galvanised and Black)	15.4kg
138 120 253	Ragged (Galvanised and Colour)	15.4kg
138 120 254	Flanged (Galvanised)	11.7kg
138 120 255	Flanged (Galvanised and Black)	11.7kg
138 120 256	Flanged (Galvanised and Colour)	11.7kg

Accessories and installation parts

138 100 994	M12 Expanding Bolt (3 required per bollard)
-------------	---------------------------------------------

Product details

1000mm above ground
 400mm below ground (ragged only)
 114mm diameter tube
 3mm wall thickness

Installation & use

Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm³) by means of three M12 bolts.
 Ragged bollards require a hole of at least 400mm deep for casting into concrete.
 AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them.
 This product is guaranteed for 12 months (*if installed and used correctly*).