



## The AUTOPA Swing Height Restrictor with Swing Gate

The AUTOPA Swing Height Restrictor with Swing Gate is perfect for controlling access at retail park entrances. With a standard clearance of 2.05m it presents an effective barrier to vehicles of all sizes, but can be opened as required to allow access to any vehicle.

Manufactured from galvanised mild steel, the system is coated red as standard (other colours are available upon request; please state BS/RAL numbers at time of order). The boom of the restrictor and the gate can both be locked in the closed and open positions (additional catch post required) using padlocks (available separately). A Knocking Bar and/or a Maximum Height Warning Sign can be added upon request. Available ragged or flanged.

### Options

Order Code	Description	Weight
138 106 690	3m Galvanised and Colour (Flanged)	113.8kg
138 106 692	4m Galvanised and Colour (Flanged)	130.5kg
138 106 694	5m Galvanised and Colour (Flanged)	145.3kg
138 106 696	6m Galvanised and Colour (Flanged)	160.1kg
138 106 698	7m Galvanised and Colour (Flanged)	177.4kg

### Accessories & installation parts

138 500 725	3m Knocking Bar	8.0kg
138 500 730	4m Knocking Bar	11.0kg
138 500 735	5m Knocking Bar	15.4kg
138 500 740	6m Knocking Bar	18.7kg
138 500 558	Height Restrictor Catch Post	24.2kg
138 100 991	M16 Expanding Bolt	
138 106 287	Maximum Height Warning Sign	
138 100 906	40mm Brass Padlock with 2 Keys	

### Product details

Main Body: 120mm x 120mm square tube  
 Main Gate Arm: 60mm x 60mm square tube  
 Knocking Bar: 48mm diameter tube  
 Standard Clearance: 2.05m  
 3mm wall thickness

### Installation & use

Ragged Height Restrictors & Catch Posts require an excavated hole of at least 600mm<sup>3</sup> for casting into concrete per leg.  
 Flanged Height Restrictors & Catch Posts require bolting down to a suitable concrete surface (not less than 600mm<sup>3</sup>) by means of four M16 bolts per leg.  
 It is recommended that suitable signs are installed to ensure vehicles are aware of the obstruction.  
 This product is guaranteed for 12 months (if installed and used correctly).



[www.autopa.co.uk](http://www.autopa.co.uk)  
 +44 (0)1788 550556

AUTOPA Limited  
 Cottage Leap, Rugby, Warwickshire CV21 3XP

