





ACP3 (galvanised)



ACP4 (galvanised)



ACP5 (galvanised)



ACP6 (stainless)

The AUTOPA Column Protector

Functional and robust in design, AUTOPA's range of column protectors are designed to protect corners, columns, and other vulnerable pillars from vehicle damage in a busy industrial environment. Our Column Protectors are manufactured from mild steel and galvanised to ensure their longevity. Suitable for both internal and external use.

Column Protectors are available in galvanised, galvanised and coated, and stainless steel finishes (RAL/BS numbers must be specified at time of order). Optional reflective tape can be added to maximise visibility.

Supplied ragged as standard, flanged versions are also available.

Product Range		
Order Code	Description	Weight
138 177 725	Galvanised ACP3 Column Protector (Flanged)	13.0kg
138 177 735	Galvanised ACP4 Column Protector (Flanged)	14.0kg
138 177 745	Galvanised ACP5 Column Protector (Flanged)	8.0kg

Accessories & installation parts

- 138 100 994 M12 Expanding Bolt
- 138 100 955 150mm x 750mm Reflective Tape

Product details

ACP3

500mm above ground 480mm outside width 460mm inside width 250mm inside clearance to back 80mm x 80mm square upright 64mm horizontal bar diameter Single height Two legs ACP4 900mm above ground 510mm outside width 380mm inside width 350mm inside clearance to back 60mm upright diameter 48mm horizontal bar diameter Double height Two legs ACP5 500mm above ground 510mm outside width 380mm inside width 350mm inside clearance to back 64mm upright diameter 48mm horizontal bar diameter Single height Two legs

ACP6 (stainless only) 185mm above ground 320mm outside width

224mm inside width 115mm inside clearance to back 48mm upright diameter 48mm horizontal bar diameter Single height Two legs

Installation & use

Flanged Column Protectors require bolting down to a suitable concrete surface (no less than 300mm³ per leg) using M12 bolts. Ragged Column Protectors require a hole of at least 250mm deep per leg for casting into concrete. Ragged versions are supplied with welded fixing spikes to ensure firm ground anchorage. This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk +44 (0)1788 550556

bsi, 9001 Quality Management
Biological EM3007 Biological Bi

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP