



# Bentham Cycle Shelter



The Bentham shelter is a free-standing, double sided cycle shelter designed for on site assembly, constructed from galvanised steel and PET sheet. The frame is made entirely from galvanised mild steel.

The rolled round tube legs offer an elegant yet strong frame that emphasises the modern aesthetic of the shelter, the Bentham shelter is an ideal basis for sheltered cycle parking needs in public spaces.



| <u>Part Number</u> | <u>Description</u>                                | <u>Weight (kg)</u> |
|--------------------|---|--------------------|
| 138 204 561        | 2m Main Bay, Bolt down                            | 228.0kg            |
| 138 204 551        | 3m Main Bay, Bolt down                            | 273.0kg            |
| 138 204 554        | 4m Main Bay, Bolt down                            | 318.0kg            |
| 138 204 563        | 5m Main Bay, Bolt down                            | 364.0kg            |
| 138 204 562        | 2m Extension Bay, Bolt down                       | 151.0kg            |
| 138 204 552        | 3m Extension Bay, Bolt down                       | 197.0kg            |
| 138 204 555        | 4m Extension Bay, Bolt down                       | 242.0kg            |
| 138 204 564        | 5m Extension Bay, Bolt down                       | 288.0kg            |
| 138 101 010        | Pack of 16 M16 Expanding bolts (for fixing 3-5m)  |                    |
| 138 101 012        | Pack of 24 M16 Expanding bolts (for fixing 6-8m)  |                    |
| 138 101 014        | Pack of 32 M16 Expanding bolts (for fixing 9-10m) |                    |

## Product details

- 76mm round and 50mm square galvanised steel tube
- 4mm clear PET sheet
- Also available ragged for casting into concrete
- Colour coated options available extra
- Extendable to any length using extension bays

## Installation & use

Each shelter leg requires bolting down to a suitable concrete surface (no less than 1,600 x 500 x 400mm) by means of eight M16 anchor bolts. The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes.

On-site assembly requires construction skill.

This product is guaranteed for 12 months (if installed and used correctly).



[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556

AUTOPA Limited  
Cottage Leap, Rugby, Warwickshire CV21 3XP

