

Fixed Post 750mm Above Ground 129mm - 204mm Diameter Stainless Steel



Diameter and Fixing Detail

138 000 140	129mm (Concrete In)
138 000 141	129mm (Bolt Down)
138 000 145	139mm (Concrete In)
138 000 146	139mm (Bolt Down)
138 000 150	154mm (Concrete In)
138 000 152	154mm (Bolt Down)
138 000 155	168mm (Concrete In)
138 000 156	168mm (Bolt Down)
138 000 160	204mm (Concrete In)
138 000 161	204mm (Bolt Down)

Product details

750mm tall

Part Number

Cast in posts 250mm below ground

- Grade 316 versions available
- Reflective bands available

Installation & use

Bolt down Fixed Posts require bolting down to a suitable concrete surface (no less then 400mm3). 48mm - 114mm three M12 bolts, 139mm - 193mm three M16 bolts. Concrete In Fixed Posts are supplied with welded fixing spikes to ensure firm ground anchorage. Concrete In Fixed Posts require an excavated hole (no less than 300mm deep) for installation. This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556



AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP

FM 31071 EMS 503166 OHS 55210