



Sheffield Cycle Stand Stainless Steel



The tubular cycle stand, a familiar sight throughout the UK, allows the frame of the bicycle to be secured by the users own security lock. Suitable for securing two bicycles.

The practical and durable nature of the VELOPA Sheffield cycle stand ensures it has been consistently recommended by cycling groups since its introduction in the 1990's.



Part Number	Description	Weight (kg)
138 200 107	Stainless Steel (Grade 304), Concrete in	9.7kg
138 200 106	Stainless Steel (Grade 304), Bolt down	8.2kg
138 200 108	Stainless Steel (Grade 316), Concrete in	9.7kg
138 200 100	Stainless Steel (Grade 316), Bolt down	8.2kg
138 101 000	M12 Stainless Steel Expanding Bolt (6 required per stand)	

Product details

- 48mm diameter
- Concrete in version 300mm below ground
- 750mm x 800mm (height x length)

Installation & use

Bolt down cycle stand require bolting to established concrete (no less than 300mm³) by means of six M12 bolts per stand.

Concrete in cycle stands require an excavated hole (no less than 300mm³) for installation.

Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction.

This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP

