

Winterbourne Wall Attached Waiting / Entrance Shelter

Accentuates any doorway or main entrance

- Protect your entrances from wet weather, dust and debris
- Can be modified to include integral guttering and drainage systems
- Ideal for use outside a main or side entrance of a building to create an outside eating area
- Clear roof and open sides gives shelter a light and airy feel
- Steel construction is long lasting and hard wearing

Specifications:

Frame:

- Mild steel, hot dip galvanised to ISO 1461 2009 and polyester epoxy powder coated
- 75mm uprights and 40mm or 50mm square hollow tubes for frame
- Maintenance free for 15 years and life maintained for 25 years
- Available in 8 standard colours (see below). All RAL colours available on special order

Roof Glazing:

- 4mm polycarbonate face fixed to frame
- 16mm triple wall polycarbonate roof

Configurations and Assembly:

- Surface (bolted) or subsurface mounted depending on size and configuration
- Preparation Required (if sub surface fixing base needed):

0.5m deep hole per leg to be filled with concrete (Allow one week for concrete to cure before assembly). Hole diameter will differ depending on shelter configuration

- · All fixings zinc plated
- Supplied with full assembly instructions
- Can be made to any size and configuration
- Can be installed by our installation team. Call us on **0800 1777 052** for a quotation





See page 2 for more information about our guarantees



Our in-house installation team have over 15 years experience and are all members of the Construction Skills Certification Scheme (CSCS). From around works to full installation, our installers are reliable, responsible and will ensure your area is left clean and tidy once the installation is complete ensuring that minimal disruption is caused to your day.

Prices from £ 106 per square metre*

Call us on 0800 1777 052 to request a FREE site survey or quotation