

beaufort flags



ISO 9001:2008



ISO 14001:2004



contoured stone appearance

- Manufactured with a contoured face
- Lightly embossed and finished with a subtle sparkle
- Superb hard-wearing surface
- Natural, muted colour range
- Significantly reduced efflorescence
- Resembles the aesthetics of natural stone
- Contemporary appearance

product specifications

Product type	Concrete Paving Flag
Manufactured to	BS EN 1339:2003
Surface layer	Hard wearing surface layer with a minimum of 4mm and >390kgs/m ³ cement
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	> 3.5MPa
Slip/Skid resistance	Extremely Low (>75 USRV)
Installed to	BS 7533-4:2006
BSI Plus	Q25 315
Applications	Suitable for all pedestrian areas and traffic-free zones. Always refer to BS 7533-8:2003 for guidance on the correct flag size to suit your application.
Energy used	100% renewable energy
Water used	100% water used from rainwater harvesting system
Carbon Footprint	400x400x40mm: 18kgCo ₂ e/m ² 600x400x40mm: 17kgCo ₂ e/m ²
Recyclable	100% of this product can be recycled
Manufacturing location	Produced in the UK with locally sourced materials
breedon rating www.bre.co.uk	A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved by using a recycled sub-base.
Tobermore products are manufactured in accordance with an accredited ISO 9001:2008 quality system. Manufacturing facilities are accredited to ISO14001:2004 Environmental Management. The company publish Environmental labels and declarations in accordance with BS EN ISO 14021:2001.	

colours



Beaufort Flags Buff

product	size (mm)	finish	edge	colours available	in stock	no. per m ²	no. per pack	weight (kg) per pack
BEAUFORT FLAGS	400 x 400 x 40	CONTOURED	CHAMFERED	Buff, Charcoal, Natural	YES	6.25	25	403
	600 x 400 x 40	CONTOURED	CHAMFERED	Buff, Charcoal, Natural	YES	4.16	25	569

Refer to all instructions and warnings on our website