mayfair flags

vibrant granite appearance

Air Clean



- Manufactured with sparkling natural granite aggregates
- Superb hard-wearing granite surface
- Vibrant long-lasting colours
- Significantly reduced efflorescence
- Creates a striking, contemporary look
- Step Flags are available

product specifications


product specilic	aliui 15								
Product type	Concrete Paving Flag								
Manufactured to	BS EN 1339:2003								
Surface layer	Hard wearing surface layer with a minimum of 4mm and >390kgs/m³ cement								
Granite content	Not less than 57% of granite aggregate in surface layer for Silver, Graphite and Russet; Not less than 46% of granite aggregate in surface layer for Sandstone; Not less than 32% of granite aggregate in surface layer for Rose								
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence								
Strength	Less than 50mm deep > 3.5MPa								
	Greater than 50mm deep >5MPa (Class 3)								
Slip/Skid risk	Extremely Low (>75 USRV)								
Installed to	BS 7533-4:2006								
N55 Plus	Q25 315								
Applications	Suitable for all pedestrian areas and traffic-free zones. Some of these specific sizes are suitable for occasional vehicular overrun. Always refer to BS 7533-8:2003 for guidance on the correct flag size to suit your application.								
Energy used	100% renewable energy								
Water used	100% water	100% water used from rainwater harvesting system							
Carbon Footprint		35mm	40mm	50mm	65mm	70mm			
* kgCo²e/m²	Silver Sandstone Graphite Russet Rose	14* 15* 15* 15* 15*	16* 17* 17* 17* 17*	19* 22* 24* 22* 22*	24* 28* 30*	30* 32* 32* 32* 32* 32*			
Recyclable	100% of this	•							
Recycled content				50mm					
(Not less than %)	Silver Graphite Russet	22% 22% 22%	20% 20% 20%	16% 16% 16%	12% 12% -	11% 11% -			
Manufacturing location	Produced in the UK with locally sourced materials								
breeom rating www.bre.co.uk	A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved by using a								

Tobermore products are manufactured in accordance with an accredited ISO 9001:2008 quality system. Manufacturing facilities are accredited to ISO14001:2004 Environmental Management. The company publish Environmental labels and declarations in accordance with BS EN ISO 14021:2001.

recycled sub-base.

colours













product	size (mm)	finish	edge	colours available	in stock	no. per m²	no. per pack	weight (kg) per pack
MAYFAIR FLAGS BIM	600 x 600 x 50	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	2.78	20	859
	600 x 400 x 50	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.16	20	589
				Rose, Russet	SPECIAL ORDER			
	450 x 450 x 70	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.94	15	512
	450 x 450 x 50	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.94	20	470
	450 x 450 x 35	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.94	30	529
	400 x 400 x 40	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver, Rose, Russet	YES	6.25	25	384
	400 x 400 x 65	GRANITE TEXTURED	CHAMFERED	Graphite, Silver	YES	6.25	16	395
				Sandstone	MADE TO			