

Turfstone


Grass paving system.

Turfstone is a ground reinforcement grass paving system ideal for occasional car parking or emergency vehicle access where the addition of grass is an attractive feature. The honeycombed cavities are designed to facilitate the growth of grass.

- Honey-combed cavities are designed to facilitate the growth of grass
- Functions as a SuDS permeable pavement

Turfstone typical applications:

- Vehicular access for occasional usage (emergency vehicle and utility access)
- Overspill car parking with infrequent trafficking (sports clubs, cemeteries, caravan parks)
- Nature reserves, sensitive heritage sites and country parks
- Road verges
- Environmental erosion control areas such as riverbanks and waterways
- Field entrances and farm tracks
- SuDS schemes



600 x 400mm

Sizes



100mm

Depths

Ef-Stop®

ST

Standard

Finish



Pedestrian
Use



Light
Traffic



Commercial
Traffic

Refer to relevant guidance in BS 7533



Turfstone



Specification



Product type	Concrete Paving Block
Manufactured to	BS EN 771-3: 2011
Surface Finish	Standard
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	Typical tensile splitting strength of >5MPa (Class 3)
Slip/Skid risk	Extremely Low
Installed to	Specific installation guidelines are available from Tobermore
BS	Plus Q25 345 Create 45-20-64/390
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 5%
Carbon Footprint	24kgCo ₂ e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breeam rating www.bre.co.uk	Refer to the Green Guide to Specification, 4 th Edition 2009.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:1026 and BES 6001.

Stock

product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per m ²	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Turfstone	600 x 400 x 100	Natural	Yes	7.68	3.84	4.17	32	1070	1060

Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk