


Kerb Small (KS)

Versatile, small smooth kerb.

Kerb Small is a dual-purpose profile available in a range of solid and blended long-lasting colours. This versatile alternative to traditional concrete kerbs offers a variety of laying possibilities.

- Versatile alternative to traditional concrete kerbs
- Dual-purpose profile offers various laying options (splayed or bullnosed)
- Vibrant long-lasting colours
- Kerb Small Specials are available



Size

Ef-Stop®





Finish





Kerb Small (KS)



Specification ✓ Ef-Stop*

Product type	Concrete Kerb					
Manufactured to	BS EN 1338:2003					
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence					
Strength	Typical tensile splitting strength of >3.6MPa					
Installed to	BS7533-6:1999					
กรร	Plus Q10 150 Create 45-20-64/370					
Applications	Residential and Commercial when designed in accordance with the latest British Standard. Available from www.bsigroup.com					
Energy used	100% renewable energy					
Water used	100% from our rainwater harvesting system and groundwater bore hole					
Recycled content	Not less than 10%					
Carbon footprint	11kgCo ² e/LM					
Recyclable	100% of this product can be recycled					
Manufacturing & Delivery	From one location within the UK					
www.bre.co.uk	Refer to the Green Guide to Specification, 4th Edition 2009.					

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 quality. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Stock

product	size (mm)	colours available	in stock	lm per pack	Im per slice	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Kerb Small	125 x 127 x 100	Bracken, Brindle, Charcoal, Heather	YES	43.2	5.4	432	1505	1505

Heather Bracken Brindle







Charcoal

