

Country Stone

Rugged stone effect.

Country Stone has a nostalgic appearance, with a rugged finish emulating the distinct aesthetics of natural stone.

- Emulates natural stone
- Vibrant long-lasting colours
- Creates a classic, vintage look

 **Ef-Stop**



375 x 100 x 140mm



240 x 100 x 140mm



225 x 100 x 140mm



200 x 100 x 140mm



160 x 100 x 140mm

Sizes (all in one pack)



375 x 100 x 65mm



300 x 100 x 65mm



225 x 100 x 65mm



375 x 100 x 140mm



300 x 100 x 140mm



225 x 100 x 215mm



440 x 100 x 215mm



300 x 100 x 215mm

Sizes (individual)

Country Stone



Specification



Product type	Concrete Block
Manufactured to	BS EN 771-5:2011
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	Typical tensile splitting strength of > 20N/mm ² mean
Installed to	BS 5628-3:2005
Shrinkage (Moisture Movement)	0.41mm/m
Durability (Freeze/Thaw)	F2 (Severe Exposure)
Tolerances	Category D1
Reaction to fire	A1
Water absorption by capillary	3g/ (m ² x s)
Water absorption	<7% water absorption on average
Water vapour diffusion coefficient	30/100 μ
Net dry density	2210 kg/m ³
Gross dry density	2200 kg/m ³
Shear bond strength	0.15N/mm ²
Thermal Conductivity	Protected 1.25W/m K Exposed 1.43W/m K
Mortars & Expansion Joints	Refer to BS 5628-3:2005
Bed Reinforcement	Refer to BS 5628-3:2005
BS5	Plus F10 295 Create 45-80-50/322
Applications	Above ground, main external wall construction, boundary walls, columns and partitions.
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 5%
Carbon footprint	36kgCo ² e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breem rating www.bre.co.uk	A+ , according to the Green Guide to Specification, 4th Edition 2009.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Contact Us

GB: 0844 800 5736
 NI: 028 7964 2411
 ROI: 048 7964 2411

Email

technical@tobermore.co.uk
 sales@tobermore.co.uk

tobermore.co.uk

Country Stone



Stock


product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
Country Stone (single course mixed length) (all sizes in one pack)	375 x 100 x 140	Bracken, Heather, Slate	YES	6.72	1.34	40	1560	1560
	225 x 100 x 140					40		
	160 x 100 x 140					40		
	240 x 100 x 140					40		
	200 x 100 x 140					40		
Country Stone (single sizes) BIM	375 x 100 x 65	Bracken, Slate	YES	6.44	0.59	264	1460	1460
	300 x 100 x 65	Bracken, Slate	YES	6.86	0.62	352	1540	1540
	225 x 100 x 65	Bracken, Slate	YES	5.15	0.47	352	1150	1150
	375 x 100 x 140	Bracken, Slate	YES	6.3	1.26	120	1456	1456
	300 x 100 x 140	Bracken, Slate	YES	6.72	1.34	160	1546	1546
	225 x 100 x 140	Bracken, Slate	YES	5.04	1.01	160	1147	1147
	440 x 100 x 215	Bracken, Slate	YES	6.05	1.51	64	1357	1357
	300 x 100 x 215	Bracken, Slate	YES	6.19	2.06	96	1428	1428
Country Stone Coping	208 x 300 x 80	Bracken, Heather, Slate	YES	-	-	128	1416	1416

BIM - This product is available to download from our website in BIM Level 2 format.

Heather



Bracken



Slate



Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk