


# Artro

Versatile, contemporary paving.

Artro is a new range of trafficable paving with versatility at its core. We have created a pallet of distinctive colourways, throwing the doors open to creativity in layout and design. Inspired by the intimate scale and form of traditional European clay pavers, Artro brings the concept right up to date, providing inspirational options for landscape designers.

- Superb hard-wearing granite surface
- Vibrant long-lasting colours
- Creates a striking, contemporary look

 **PrimeTop**  **Ef-Stop**



# Artro



## Specification

 **PrimeTop**  **Ef-Stop**

<b>Product type</b>	Concrete Paving Block	
<b>Manufactured to</b>	BS EN 1338:2003	
<b>Surface Layer</b>	Hard-wearing surface layer with a minimum of 4mm and >350kg/m <sup>3</sup> cement	
<b>Surface Finish</b>	Textured Granite Aggregate	
<b>Granite Content</b>	Not less than 53% of granite aggregate in surface layer for Silver, Mid Grey, Graphite	
<b>Spacer</b>	Unique VS5 spacer which adds shift protection on five sides of the block	
<b>Efflorescence</b>	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence	
<b>Strength</b>	Typical tensile splitting strength of >3.6MPa	
<b>Slip/Skid risk</b>	Extremely Low	
<b>Installed to</b>	Specific installation instructions are available from Tobermore	
<b>BS</b>	<b>Plus</b> Q24 110 <b>Create</b> 45-20-64/400	
<b>Applications</b>	Refer to the relevant part of BS 7533 for the correct sub-base design for your application. Available from <a href="http://www.bsigroup.com">www.bsigroup.com</a>	
<b>Energy used</b>	100% renewable energy	
<b>Water used</b>	100% from our rainwater harvesting system and groundwater bore hole	
<b>Recycled content</b>	Not less than 6%	
<b>Carbon Footprint</b>	<b>Silver</b>	40kgCo <sup>2</sup> e/m <sup>2</sup>
	<b>Graphite</b>	43kgCo <sup>2</sup> e/m <sup>2</sup>
	<b>Mid Grey</b>	43kgCo <sup>2</sup> e/m <sup>2</sup>
<b>Recyclable</b>	100% of this product can be recycled	
<b>Manufacturing &amp; Delivery</b>	From one location within the UK	
<b>Green rating</b> <a href="http://www.bre.co.uk">www.bre.co.uk</a>	Refer to the Green Guide to Specification, 4 <sup>th</sup> Edition 2009	

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

### Contact Us

GB: 0844 800 5736  
 NI: 028 7964 2411  
 ROI: 048 7964 2411

### Email

[technical@tobermore.co.uk](mailto:technical@tobermore.co.uk)  
[sales@tobermore.co.uk](mailto:sales@tobermore.co.uk)

[tobermore.co.uk](http://tobermore.co.uk)



# Artro



## Stock

product	size (mm)	colours available	in stock	m <sup>2</sup> per pack	m <sup>2</sup> per slice	weight kg per pack GB	weight kg per pack NI/ROI
<b>Artro</b>	220x55x80	Platinum, Steel, Carbon, Autumn, Heather, Bracken, Slate	YES	6.776	0.847	1266	1266

**Platinum**




**Steel**



**Carbon**



**Autumn**



**Heather**



**Bracken**



**Slate**



**Contact Us**

GB: 0844 800 5736  
 NI: 028 7964 2411  
 ROI: 048 7964 2411

**Email**

technical@tobermore.co.uk  
 sales@tobermore.co.uk