

# Tegula Setts




SCAN HERE

## Traditional styling.

With Tegula Setts you can create an authentic aged effect. We manufacture Tegula Setts in two colours, so you can be even more creative with your paving design.

- Processed to give an aged, antique appearance
- Vibrant long-lasting colours
- Significantly reduced efflorescence
- Suitable for both modern or period properties
- Ideal for creating borders

90mm x VARIOUS (all sizes in one pack)



100mm x 100mm



50mm

Depths

## Ef-Stop®



Aged

Finish



Pedestrian Use



Light Traffic

Refer to relevant guidance in BS 7533



BIM Level 2



# Tegula Setts



## Specification



<b>Product type</b>	Concrete Paving Block
<b>Manufactured to</b>	BS EN 1338:2003
<b>Surface Finish</b>	Processed to give an aged appearance
<b>Efflorescence</b>	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
<b>Strength</b>	Typical tensile splitting strength of >3.6MPa
<b>Slip/Skid risk</b>	Extremely Low
<b>Installed to</b>	BS 7533-3:2005
<b>NS</b>	<b>Plus</b> Q24 110 <b>Create</b> 45-20-64/410
<b>Tolerances on Dimensions (mm)</b>	Length ±2mm, width ±2mm, thickness ±3mm
<b>Abrasion Resistance</b>	Class 3
<b>Durability (Freeze-thaw)</b>	Class 3
<b>External Fire Performance</b>	Deemed to satisfy. See Commission Decision 2000/553/EC
<b>Reaction to fire</b>	Class A1
<b>Applications</b>	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from <a href="http://www.bsigroup.com">www.bsigroup.com</a>
<b>Energy used</b>	100% renewable energy
<b>Water used</b>	100% from our rainwater harvesting system and groundwater bore hole
<b>Recycled content</b>	Not less than 10% (all colours except Natural & Golden)
<b>Carbon Footprint</b>	17kgCo <sup>2</sup> e/m <sup>2</sup>
<b>Recyclable</b>	100% of this product can be recycled
<b>Manufacturing &amp; Delivery</b>	From one location within the UK
<b>breeam rating</b> <a href="http://www.bre.co.uk">www.bre.co.uk</a>	<b>A</b> , according to the Green Guide to Specification, 4 <sup>th</sup> Edition 2009. <b>A+</b> can be achieved when used in conjunction with a prepared recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

### Contact Us

GB: 0844 800 5736  
NI: 028 7964 2411  
ROI: 048 7964 2411

### Email

[technical@tobermore.co.uk](mailto:technical@tobermore.co.uk)  
[sales@tobermore.co.uk](mailto:sales@tobermore.co.uk)

[tobermore.co.uk](http://tobermore.co.uk)

# Tegula Setts



## Stock

product	size (mm)	colours available	in stock	m <sup>2</sup> per pack	m <sup>2</sup> per slice	no. per m <sup>2</sup>	no. per pack	weight kg per pack GB	weight kg per pack NI/ROI
<b>Tegula Setts</b> BIM	Various x 50	Charcoal, Golden	YES	8.5	0.85	117	995	930	920
	100 x 100 x 50	Charcoal, Golden	YES	11.52	0.96	100	1152	1215	1205

**BIM** - This product is available to download from our website in BIM Level 2 format.

### Charcoal



### Golden



### Contact Us

GB: 0844 800 5736  
 NI: 028 7964 2411  
 ROI: 048 7964 2411

### Email

technical@tobermore.co.uk  
 sales@tobermore.co.uk