



**HiSec DualSkin Q40**

**Manufacturer: Zaun Limited**

**Web:               www.zaun.co.uk**

**Tel:                +44 (0)1902 796699**

**Product reference:**

HiSec DualSkin.

**Height:**

[ \_\_\_\_\_ ] - 0.60–5.2 m, insert requirements.

**Gates:**

Pedestrian:

[Not required].

[Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements.

Vehicular:

[Not required].

[Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

**Guidance for HiSec DualSkin from Zaun Limited**

More about HiSec DualSkin: As standard

As standard

**Finish:**

Galvanized and polyester powder coated.

# ZAUN

**Mesh:**

HiSec mesh comprising of two panels of 12.7 x 12.7 mm mesh with single 4 mm vertical wires at 12.7 mm centres and horizontal wires at 12.7 mm centres.

**Posts:**

Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm centres.

**Post to panel fixing:**

Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 50 mm centres. The full height clamp bars create a safe finish with the mesh ends behind the clamp bar.

**Gates:**

Framed in a 100 x 50 mm RHS, with Zaun HiSec DualSkin mesh bolted onto the frame using the Zaun picture frame design, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with drop bolts.