

## Manufacturer: Zaun Limited Web: www.zaun.co.uk Tel: +44 (0)1902 796699 **Product reference:** [Advantage Tennis 6]. - With 6 mm horizontal wires. [Advantage Tennis 8]. - With 8 mm horizontal wires. Height: [\_\_\_\_\_] - 2.43–6.0 m, insert requirements. Fixing: [Bolt down]. [In ground]. [Wall]. Gates: Pedestrian: [Not required]. [Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements. Vehicular: [Not required]. [Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements.

**Advantage Tennis Q40** 



## **Guidance for Advantage Tennis from Zaun Limited**

More about Advantage Tennis: As standard

As standard
Finish:
Galvanized and polyester powder coated.
Mesh:
- Advantage Tennis 6:
Advantage Tennis 6 mesh comprising $42.85 \times 200 \text{ mm}$ with dual 6 mm horizontal wires at 200 mm centres with single 5 mm vertical wires at $42.85 \text{ mm}$ centres.
- Advantage Tennis 8:
Advantage Tennis 8 mesh comprising $42.85 \times 200 \text{ mm}$ mesh with dual 8 mm horizontal wires at 200 mm centres with single 6 mm vertical wires at $42.85 \text{ mm}$ centres.
Posts:
Rectangular hollow section (RHS) sports posts - sizes dependent on height, spaced at 2525 mm centres, consult manufacturer.
Post to panel fixing:
Panels fixed to posts with full height $40 \times 5$ mm clamp bar with bolt fixings at $200$ mm centres with EPDM inserts. The full height clamp bars create a flush safe finish with the mesh ends behind the clamp bar.
Gates:
Framed in a 50 $\times$ 50 mm RHS with Advantage Tennis mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts.