

Manufacturer: Zaun Limited Web: www.zaun.co.uk Tel: +44 (0)1902 796699 **Product reference:** Duo6 Sports. Height: [_____] - 0.630–6.0 m, insert requirements. Fixing: [Bolt down]. [In ground]. [Wall]. Gates: Pedestrian: [Not required]. [Required]. - Single leaf, 1.2 m wide, or width to suit, consult manufacturer and insert requirements. Vehicular: [Not required]. [Required]. - Double leaf, 3.0 m wide, or width to suit, consult manufacturer and insert requirements. **Projection:**

Duo6 Sports Q40

[Minimal].



[Standard].
Guidance for Duo6 Sports from Zaun Limited
More about Duo6 Sports: As standard
As standard
Finish:
Galvanized and polyester powder coated.
Mesh:
Duo6 mesh comprising 50×200 mm mesh with dual 6 mm horizontal wires at 200 mm centres and single 5 mm vertical wires at 50 mm centres.
single 3 min vertical wires at 30 min centres.
Posts:
Various rectangular hollow section post (RHS) sizes dependent on height, spaced at 2525 mm
centres.
Post to panel fixing:
Panels fixed to posts with full height 40×5 mm clamp bar with bolt fixings at 200 mm centres with EPDM inserts. The full height clamp bars create a flush safe finish with the mesh ends behind the
clamp bar.
Gates:
Framed in a 50 x 50 mm RHS with Zaun Duo8 mesh welded inside the frame, with slide latch. Gate supplied with rubber bump stop and two suitable gate posts. Vehicular access also supplied with

drop bolts.