



Designed to be a strong and durable construction, Barkers Palisade fencing provides excellent protection against climbing and cut-through. Palisade fencing with either a 'D' or a 'W' profile to varying specifications including Gas, Water & Electric Companies and Public Sector specifications.



PALISADE BARKERS FENCING PALISADE RANGE

AVAILABLE FROM STOCK SEE PAGE 6

Standard sizes						
Panels						
Fence heights m	Post Centres mm	Pale thickness mm	Pales per bay mm	Rails Cross rails mm	Posts Overall length mm	Post Section mm
1.2	2.75	2	17	45 x 45 x 6	1700	100 x 55
1.5	2.75	2	17	45 x 45 x 6	2000	100 x 55
1.8	2.75	2/2.5	17	45 x 45 x 6	2300	100 x 55
2	2.75	2/2.5/3	17	50 x 50 x 6	2700	100 x 55
2.1	2.75	2/2.5/3	17	50 x 50 x 6	2700	100 x 55
2.4	2.75	2/2.5/3/3.5	17	50 x 50 x 6	3100	100 x 55
3	2.75	2/2.5/3/3.5/3.9	17	65 x 50 x 6	3900	100 x 55 or 127 x 76

Heights

1.2m, 1.5m, 1.8m, 2m, 2.1m, 2.4m 3m and 3.6m heights are available.

Paling tops

Can be single pointed, triple pointed, square tops, round and notched tops or rounded only.

Horizontals

Available in 3 standard sizes according to height and site requirements: 45x45, 50x50 and 65x50mm.

Posts

Available with welded fishplates or slotted, complete with loose fishplates that can be concreted-in, base plated for bolting down or cranked. Posts can be vertically extended to take barbed or razor wire.

Panels

Panels can be easily raked to allow for most site conditions, and can also be welded at our factory for added security.

Fixings

All fixings are anti-vandal.

Gates

Standard gates are available or tailored-made to suit your requirements including: Locinox locks, **HYDRACLOSE** self-closers, razor wire extensions and other bespoke items to suit your needs. All gates are supplied with rear hung adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions complete with anti-climb protection.

Paling thickness

- 'W' profile 2.0mm - commercial specification.
- 'W' profile 2.5mm - general purpose to BS: EN: 1722 Pt 12.
- 'W' profile 3.0mm - security purpose to BS: EN: 1722 Pt 12.
- 'D' profile 3.0mm - general purpose to BS: EN: 1722 Pt 12.
- 'D' profile 3.5mm - security purpose to BS: EN: 1722 pt 12.
- 'D' profile 3.9mm - security purpose to BS: EN: 1722 pt 12.

All our palisade gates are to BS: EN: 1722 pt 12. See our gate range for further details.

Additional security toppings

Barkers Fencing supply additional toppings for security fences including razor wire coils, razor wire tape, barbed wire, rotating spikes. We can also prepare fence posts to take electric security fence on the back and work closely with the major electric security fence manufacturers.

