



KÖSTER Gel Pump

Technical Data Sheet / Prod. code IN 928 001

Issued: 2015-02-26

Electrical 2 component injection pump for the injection of KÖSTER PUR Gel

Features

The KÖSTER Gel Pump is a reliable electrically driven, two-component injection pump which is suited for injection of KÖSTER PUR Gel.



Mixing ratio Gel : Water	Total	Output ratio l / min.
1 : 1	2 Liter	1.67
1 : 2	3 Liter	2.50
1 : 4	5 Liter	2.08
1 : 5	6 Liter	2.00
1 : 8	7 Liter	1.88
1 : 10	11 Liter	1.83
1 : 13	14 Liter	1.79

Packaging

IN 928 001 piece

Related products

KÖSTER PUR Gel	Prod. code IN 285
KÖSTER Impact Packer 18 plus	Prod. code IN 904 001
KÖSTER Injection Lance	Prod. code IN 924 001
KÖSTER Distributor Lance	Prod. code IN 926 001
KÖSTER Water Hose for Gel Pump	Prod. code IN 928 002
KÖSTER Gel Hose for Gel Pump	Prod. code IN 928 003
KÖSTER Manometer for Gel Pump	Prod. code IN 928 004
KÖSTER Mix head for Gel Pump	Prod. code IN 928 005
KÖSTER Injection Whip for Gel Pump	Prod. code IN 928 006
KÖSTER Slide Coupling for pan-head fitting	Prod. code IN 928 007
KÖSTER Swivel Joint	Prod. code IN 928 008

Technical Data

Measurements	
Width	68 cm
Height	78 cm
Depth (folded)	95 cm
Depth (unfolded)	140 cm
Weight	60 kg
Operating pressure	approx. 20 bar
Electrical connection	230 V, 50 Hz
Material hopper for Gel	5 kg
Static suction lift	2 m
Hose length (HD-hose)	5 m
Delivery rate (both sides 100 %)	approx. 2.5 l / min
Mixing ratio (continuous)	1:1 to 1:15

Application

The instructions for use and a respective video are supplied together with the pump.

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.