

DELTA® protects property. Saves energy. Creates comfort.

# DELTA®-MS 20

## General-purpose seepage layer for long-term safety.

Resistant to compression and degradation in soil.

DELTA®-branded quality products made by Dörken.

Drainage system  For building construction and civil engineering  For vertical and horizontal application

### DELTA®-MS 20

#### Technical data overview:

Material	Special high-density PE
Dimple height	20 mm approx.
Compressive strength	150 kN/m² approx.
Drainage capacity	10 l/s · m approx.
Air gap between dimples	14 l/m² approx.
Service temperature range	- 30 °C to + 80 °C
Fire resistance rating	Standard flammability as per DIN 4102 class B2; optional DIN 4102 class B1 for special requirements
Roll size	20 m x 2 m

#### DELTA®-MS 20 perforated

Technical data as for DELTA®-MS 20 except		
Compressive strength	110 kN/m² approx.	
Drainage capacity at 1 cm water column	0.5 l (s x m²) 1	

DELTA®

## High drainage capacity in double-shell structures.

DELTA®-MS 20 ...

- ... is a compression-resistant, durable dimpled sheet made from special highdensity polyethylene.
- ... offers outstanding safety thanks to its
  20-mm dimples and its high drainage capacity.
- ... resists degradation in soil and chemical attack as well as being non-polluting for drinking water.
- ... may be applied as a cost-efficient horizontal or vertical permanent shuttering between a shotcrete shell or curtain wall and a concrete structural wall.
- I... drains off water emerging from the rocky subsoil when vertically applied.

- ... controls rising underground water when laid horizontally between the foundation and the surface layer of a carriageway, and conveys it towards the drain.
- ... is ideal for coping with water-related problems in tunnel construction. With the dimples facing outward, the sheet forms a continuous system of channels by which water is guided towards the drain.
- ... in the perforated version is a special high-capacity sheet for draining roof surfaces such as parking decks and roof gardens. Because of their porosity, sheets are permeable so that surplus water will drain away evenly.





Delta Membrane Systems Ltd. Delta House, Merlin Way North Weald, Epping, Essex CM16 6HR Phone: +44 (0)1992 523 523 Fax: +44 (0)1992 523 250 info@deltamembranes.com www.deltamembranes.com

ñ

**DELTA®-MS** 

A company of the Dörken Group.

DELTA® is a registered trademark of Ewald Dörken AG, Herdecke, Germany.